

Part Number: SL12 50002

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL12 50002-A



Electrical Specifications:

Resistance @ 25°C	50.0 Ω \pm 20%
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	20.0 J
Actual Failure Point of Instantaneous Energy (Joules)	40.0 J
Resistance @ 100% of Max Current	0.650 Ω
Resistance @ 50% of Max Current	1.330 Ω
Body Temperature @ 100% Current Rating	142 °C
Dissipation Constant	12.7mW/°C
Thermal Time Constant	47 seconds
Resistance @ 1.60 Amps	0.720 Ω
Material Type	"T"
Max Recommended Capacitance @120VAC/240VAC	1380 μ F/350 μ F

Mechanical Specifications:

D	12.0 \pm 0.5 mm
T	5.1 \pm 0.2 mm
Lead Diameter	0.8 \pm 0.1 mm
S	7.8 \pm 2.0 mm
L	38.0 \pm 9.0 mm
Straight Leads Coating Run Down	5.0 \pm 1.0 mm
B	11.5 \pm 3.50 mm
C	3.42 \pm 0.50 mm