

Part Number: SL22 60003

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL22 60003-A



Electrical Specifications:

Resistance @ 25°C	60.0 Ω ± 25%
Max Steady State Current Up to 65°C	3.0 A
Max Recommended Energy Rating (Joules)	72.0 J
Actual Failure Point of Instantaneous Energy (Joules)	150.0 J
Resistance @ 100% of Max Current	0.409 Ω
Resistance @ 50% of Max Current	1.280 Ω
Body Temperature @ 100% Current Rating	166 °C
Dissipation Constant	32.4mW/°C
Thermal Time Constant	112 seconds
Material Type	"I"
Maximum Recommended Voltage	265 Vrms
Max Recommended Capacitance @ 120/240 VAC	4900µF/1245µF

Mechanical Specifications:

D	20.0 ± 1.0 mm
T	5.0 ± 0.5 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads Coating Run Down	5.0 ± 1.0 mm
B	9.35 ± 0.85 mm
C	3.82 ± 1.0 mm