



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

D:	37.0	± max
T:	11.0	± max
Lead Diameter	2.5	± nom
S:	19.0	± nom
L:	40.0	± nom
Coating Lead Run Down (straight Leads)	7.0	± max
B:		±
C:	7.50	± nom



**Electrical Specifications**

Resistance:	10.0 Ω	± 25 %
Max Steady State Current upto 65°C:	18.00	A
Max Rec. Energy Rating:	500	J
Actual Failure Instantaneous Energy:	1000	J
Maximum Capacitance @ 120 VAC:	34,000	µf
Maximum Capacitance @ 240 VAC:	8,683	µf
Maximum Capacitance @ 440 VAC:	2,007	µf
Maximum Capacitance @ 680 VAC:	1,000	µf
Resistance @ 100% Max Current:	0.05	Ω
Resistance @ 50% Max Current:	0.15	Ω
Body Temperature at 100% Max Current:	215.00	°c
Dissipation Constant:	78.0	mw/°c
Thermal Time Constant:	240	Sec.
Material Type (for Beta and Curve):	I	

<b>MS35 10018</b>	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A