

Industrial Power Solution

Panel Mount Power





Industrial Power/Panel Mount Single-Output Series

| Model | PFC (Y/N) | Dimension (L X W X H) | Watts | Output Voltage | Output Current | Tol. | EMC | Working TEMP. | MTBF | Safety |
|--------------|-----------|-----------------------|-------|----------------|----------------|------|---------|---------------|--------------------|------------------------------------|
| HA-1101-24NL | N | 129x97x30 | 100W | 24V | 4.5 | 0.5% | Class B | -30~+70°C | 720.6K (25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1101-12LF | Y | 179x99x30 | 100W | 12V | 8.5 | 0.5% | Class B | -30~+70°C | 288.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1101-24LF | Y | 179x99x30 | 100W | 24V | 4.2 | 0.5% | Class B | -30~+70°C | 288.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1201-12NL | N | 215X115X30 | 200W | 12V | 17.0 | 1.0% | Class B | -25~+70°C | 347.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1201-24NL | N | 215X115X30 | 200W | 24V | 8.8 | 0.5% | Class B | -25~+70°C | 347.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1201-12LF | Y | 215X115X30 | 200W | 12V | 16.7 | 0.5% | Class B | -30~+70°C | 224.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1201-24LF | Y | 215X115X30 | 200W | 24V | 8.4 | 0.5% | Class B | -30~+70°C | 224.5K(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1351-12NL | N | 215X115X30 | 350W | 12V | 29.0 | 1.0% | Class B | -25~+70°C | 327K (25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1351-24NL | N | 215X115X30 | 350W | 24V | 14.6 | 0.5% | Class B | -25~+70°C | 327K (25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| PA-1401-2LA | Y | 212x115x40 | 400W | 12V | 33.3A | 0.5% | Class B | -20~60°C | 300K, SR-332(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| PA-1401-1LA | Y | 212x115x40 | 400W | 24V | 16.7A | 0.5% | Class B | -20~60°C | 300K, SR-332(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |



Industrial Power/Panel Mount Single-Output Series(cont.)

| Model | PFC (Y/N) | Dimension (L X W X H) | Wattes | Output Voltage | Output Current | Tol. | EMC | Working TEMP. | MTBF | Safety |
|------------------|-----------|-----------------------|--------|----------------|----------------|------|---------|---------------|----------------------|------------------------------------|
| PS-2102-2LA-RoHS | Y | 247x127x63.5 | 1000W | 48V | 20.8A | 0.5% | Class B | 0~70°C | 313.1K, SR-332(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1750-12NL | N | 99x97x30 | 75W | 12V | 6.3 | 0.5% | Class B | -30~+70°C | 720.6K (25°C) | 62368 CQC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1750-24NL | N | 99x97x30 | 75W | 24V | 3.1 | 0.5% | Class B | -30~+70°C | 720.6K (25°C) | 62368 CQC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1151-12NL | N | 159x97x30 | 150W | 12V | 12.5 | 0.5% | Class B | -30~+70°C | 720.6K (25°C) | 62368 CQC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1151-12NL | N | 159x97x30 | 150W | 24V | 6.3 | 0.5% | Class B | -30~+70°C | 720.6K (25°C) | 62368 CQC/CB/CE/UL/TUB/CCC/BSMI |
| HA-1601-24LF | Y | 220x127x40 | 600W | 24V | 25.0 | 0.5% | Class B | -20~60°C | 300K, SR-332(25°C) | 62368 CCC/CB/CE/UL/TUB/CCC/BSMI |



Thank You