



Capacitor Line Card





AC Capacitors for Motor Run Applications

Product Range:

Capacitance: 2uF to 120uF

Tolerance: -6%, +6%

Voltage: 240 to 660 VAC

Op. Temp: -40°C to +70°C

Case: Aluminum

Applications:

- HVAC Equipment
- Appliances
- Office Equipment

Features:

- Proven EIA-456 Compliant 60,000 Hour Reliability
- Pressure Sensitive Interrupter (PSI)



AC Capacitors for HID Lighting Applications

Product Range:

Capacitance: 5uF to 60uF

Tolerance: -3%, +3%

Voltage: 280 to 580 VAC

Op. Temp: -40°C to +90°C
-40°C to +100°C

Case: Aluminum

Applications:

- Mercury Vapor
- Metal Halide
- High Pressure Sodium

Features:

- Proven EIA-456 Compliant 60,000 Hour Reliability
- Pressure Sensitive Interrupter (PSI)



Capacitors for AC and DC General Purpose Applications

Product Range:

Capacitance: 2uF to 120uF
Tolerance: -6%, +6%
Voltage: 240 to 660 VAC
Op. Temp: -40°C to +70°C
Case: Aluminum

Applications:

- Electronic Power Conversion
- Filtering
- Power Supply

Features:

- Proven EIA-456 Compliant 60,000 Hour Reliability
- Pressure Sensitive Interrupter (PSI)



Dry Capacitors for Motor Run Applications

Product Range:

Capacitance: 1uF to 50uF
Tolerance: -10%, +10%
Voltage: 120 to 370 VAC
Op. Temp: -40°C to +70°C
Case: Plastic

Applications:

- HVAC Equipment
- Appliances
- Office Equipment

Features:

- Proven EIA-456 Compliant 60,000 Hour Reliability
- UL Recognized Construction





Dry Capacitors for HID Lighting Applications



Product Range:

- Capacitance:** 1uF to 50uF
- Tolerance:** -3%, +3%
- Voltage:** 120 to 370 VAC
- Op. Temp:** -40°C to +90°C
- Case:** Plastic

Applications:


- Mercury Vapor
- Metal Halide
- High Pressure Sodium

Features:

- Proven EIA-456 Compliant 60,000 Hour Reliability
- UL Recognized Construction



Snubber, High Current DC, and Switching Capacitors



Product Range:

- Capacitance:** 0.01uF to 30uF
- Tolerance:** ±5%, ±10%
- Voltage:** 250 to 3,000 VAC
- Op. Temp:** -40°C to +85°C
-55°C to +105°C
- Case:** Potting Compound

Applications:

- Input/Output Filters
- Switch-Mode Power Supplies
- Un-Interruptible Power Systems

Features:

- Fire Retardant Tape



Screw Terminal Electrolytic Capacitors

Product Range:

Capacitance: 250uF to 230,000uF • Drives

Tolerance: -10%, +50% • Power Conditioning

Voltage: 50 to 450 VAC • Photoflash Lighting

Op. Temp: -40°C to +85°C
-55°C to +105°C

Case: Aluminum

Features:

- High-Gain Aluminum Foil and Reliable Safety Vent



The Genteq logo, featuring a stylized blue and white wave icon to the left of the word "genteq" in a white sans-serif font.



Snap-In Electrolytic Capacitors

Product Range:

Capacitance: 100uF to 100,000uF • Drives

Tolerance: ±20% • Power Conditioning

Voltage: 10 to 450 VAC • Photoflash Lighting

Op. Temp: -40°C to +85°C
-40°C to +105°C

Case: Aluminum

Features:

- High-Gain Aluminum Foil



The Genteq logo, featuring a stylized blue and white wave icon to the left of the word "genteq" in a white sans-serif font.





Life-Line Capacitor Kit for Motor Run Applications

Included in Kit:

- 6 best in class Genteq Motor Run Capacitors
- 2 Life-Line "Spider" Devices
- 1 Capacitor Mounting Hardware Kit
- 1 Device Mounting Hardware Kit
- 1 Robust Carrying Case



Features:

- UL Listed Life-Line "Spider" Device
- Replace 48 Different Ratings (Over 85% of models)
- Lowest Total Cost Replacement Solution
- Solves Truck Inventory Hassles



Mounting Accessories for Oil-Filled Capacitors

Universal Wrap Around Brackets:

- Oval Capacitors - 1.25", 1.50", 1.75", or 2.00" base size
- Round Capacitors - 1.75", 2.00", 2.50", or 3.00" base size

Wrap Around Brackets:

- Oval Capacitors - 1.25", 1.50", 1.75", or 2.00" base size
- Round Capacitors - 1.75", 2.00", or 2.50" base size

Footed Brackets:

- Oval Capacitors - 2.12", 2.88", 3.88", 4.75", or 5.75" in height
- Round Capacitors - 2.12", 2.88", 3.88", 4.75", or 5.75" in height



Protective Accessories for Oil-Filled Capacitors



Protective Boots:

- 60°C Temperature Rated
- 105°C Temperature Rated

