## KEMET Part Number: CDR34BX333BKWP-T&R

(C1812N333K1XPL[W]7189)



Capacitor, Ceramic, 0.033 uF, +/-10% Tol, 100 V, BX, 1812 (4532 metric)



General Information		
Supplier:	KEMET	
Application:	Military Chip per Mil-prf-55681	
Chip Size:	1812 (4532 metric)	
Temperature Coefficient:	BX	
Termination Type:	Tin-Lead (SnPb)	
RoHS:	No	

Dimensions (mm)		
Symbol	Dimension	Tolerance
Т	1.5	
L	4.5	+/-0.25
W	3.2	+/-0.25
В	0.5	+/-0.25

Specifications		
Capacitance:	0.033 uF	
Voltage:	100 V	
Tolerance:	+/-10%	
Temperature Range:	-55/+125C	
Failure Rate:	P (0.1%/1000 Hrs)	
Testing:	MIL-PRF-55681	
Miscellaneous:	Termination Description: SolderPlate 70-30	

Packaging Specifications		
Package Kind:	T&R	
Package Size:	7 in/180 mm	
Package Type:	Plastic Tape	
Package Quantity:	1100	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

