



DC POWER CONNECTORS: KPJX Series
Snap and Lock PCB Mount Receptacle

Product Features

Laptop Computers, Power Supplies and Other Portable Digital Equipment Applications
Snap & Lock Feature Helps to Prevent Accidental Disconnects
3 or 4 Pins Transmit Power, or One Pin Can Be Used For Signal Transmission
For Signal and DC Power Applications
CSA/NRTL Certified File No. LR78160
UL File No. E140125

Performance Specifications

Materials and Finish

Shield: Copper Alloy, Tin Plated
Body: PBT, UL 94V-0 Rated
HT Body: High Temperature Thermoplastic, UL 94V-0 Rated

Electrical Characteristics

Contact Rating

3 Position: Pin 1 and 2, 48V DC at 7.5A Max., Pin 3, 48V DC 1.0A Max.
4 Position: 48V DC 7.5A Max. For All Pins.
Insulation Resistance: 50 Megohms Min. at 250V DC
Dielectric Withstanding Voltage: 500V AC for 1 Minute
Contact Resistance: 30 milliohms Max.


Mechanical Characteristics

Durability: 1000 Cycles

2D Drawing	IGES	STEP	3D PDF
Check Stock	Solder Profile	Request a Sample	Send Us An Email
RoHS Compliant	REACH Compliant	UL Plastic	Certificate of Compliance

Generated Part Number

Part Number Builder



Series

KPJX - Right Angle Receptacle
KPJXHT - High Temperature, Right Angle Receptacle

Number of Contacts

3 Pin
4 Pin

Contact Type

S - Socket

Shield Option

Blank - Non-Shielded
S - Shielded

Mates with: KPPX Series Plugs

Contact Kycon for Other Options

KPJX-3S Series
Dimensions in mm

