

Interactive Catalog Supplements Catalog PDFs

If you need detailed product information, or help choosing the right product for your application, see our [Interactive Catalog](#). Use the [Interactive Catalog](#) to access the most complete and up-to-date information available.

The [Interactive Catalog](#) provides an extensive collection of product specifications, application data, and technical literature that can be searched based on criteria you select.

This PDF catalog information was published in November 2000.



Sensing and Control
[Interactive Catalog...](#)

**Click this icon to try
the Interactive Catalog.**

Sensing and Control

Honeywell Inc.

11 West Spring Street

Freeport, IL 61032

www.honeywell.com/sensing



AML42C
(Use AML52-C/-A
pushbuttons only.
Page 31.)



AML42S

| Housing Type |
|------------------------------------|
| AML42 C Square 1 LED |
| AML42 S Compact 1 LED |

| Bezel Color |
|-------------------|
| B Black |

| Yellow | | Green | |
|----------|------|----------|------|
| H | V* | R | V* |
| J | 5 V | S | 5 V |
| K | 10 V | T | 10 V |
| L | 15 V | W | 15 V |
| M | 24 V | X | 24 V |

| LED Color/ Voltage | |
|-----------------------|------|
| Red | |
| B | V* |
| C | 5 V |
| D | 10 V |
| E | 15 V |
| F | 24 V |

| Terminal Type/ Diode Protection | |
|--|--|
| 2 .110 × .020 (Solder or Q.C.) | 8 .110 × .020 w/diode to protect LED |
| 3 .025 × .025 (Printed Circuit or Push-On) | 9 .025 × .025 w/diode to protect LED |

Example: **AML42SBC2**
Compact indicator with black bezel; 5 volt
red LED; .110 × .020 termination.

* See LED application data, page 46, for these
devices without current-limiting resistor.