3.5mm PITCH & 3.81mm PITCH

TAICOM type TBP3/C & J

TAiCOM

A range of two part pluggable blocks, from 2 to 12 way, offered in 3.5mm and 3.81mm pitch. Consisting of pcb mounting socket headers and mating, rising clamp screw terminal plugs, they combine the convenience of screw connection with the ease of a plug & socket. Other ways are available to special order.



- Two part pluggable blocks
- 3.5mm & 3.81mm pitch, 8A rating
- Polarised, latched mating
- Rising clamp wire protection
- Combi screws
- · Choice of plug & socket style
- Green UL94V-0 flame retardant bodies

Specification

c**FLI®**us

Materials	
Mouldings	 Green glass filled polyamide to UI 94V-0
Terminals	10 02011 0
Screws	
Distance Islands	chromate finish
Rising clamps	. brass, iiri piated

Ratings (limited by pcb)
Current rating.....


 Voltage rating
 300Vac


 Oper. temp. range
 -33°C to +120°C (plugs)

 -40°C to +105°C (socket headers)

Dimensions (mm)

PLUGS





3.5mm PITCH & 3.81mm PITCH

PLUGS - screw terminal

Choice of straight or right angle styles fitted with rising clamp type wire protection guards. Straight has option of reversed body.

Right Angle



Т	уре
2	way
3	way
4	way
5	way
6	way
7	way
8	way
9	way
10	way
11	way
12	way

Type

2 wav

3 wav

4 wav

5 way

6 way

7 wav

8 wav 9 way

Туре 2 way

3 way

4 way

5 way

6 way

7 way

8 way

9 way

10 way

11 way

12 way

3.5mm PITCH Manf. Part No. &

iglia Order Col
TBP302CG
TBP303CG
TBP304CG
TBP305CG
TBP306CG
TBP307CG
TBP308CG
TBP309CG
TBP310CG
TBP311CG
TBP312CG

3.81mm PITCH Manf. Part No. &

iglia Order Cod
TBP302JG
TBP303JG
TBP304JG
TBP305JG
TBP306JG
TBP307JG
TBP308JG
TBP309JG
TBP310JG
TBP311JG
TBP312JG

SOCKET HEADERS - pcb mounting

3.5mm PITCH

TBP311CVC

TBP312CVC

Choice of vertical or right angle styles with closed ends.

11 way

12 way

Type 2 way

3 way

4 way 5 way

6 way

7 way

8 way

9 way

10 way

11 way

Vertical



	Manf. Part No. &
Type	anglia Order Code
2 way	TBP302CVC
3 way	TBP303CVC
4 way	TBP304CVC
5 way	TBP305CVC
6 way	TBP306CVC
7 way	TBP307CVC
8 way	TBP308CVC
9 way	TBP309CVC
10 way	TBP310CVC

3.011111111111111111
Manf. Part No. & a∩glia Order Code
TBP302JVC
TBP303JVC
TBP304JVC
TBP305JVC
TBP306JVC
TBP307JVC
TBP308JVC
TBP309JVC
TBP310JVC
TBP311JVC
TBP312JVC

3.81mm PITCH

Straight



Wire entry on the 10 way coding/smooth side 11 way of the plug. 12 way

3.5mm PITCH

anglia Order Cod
TBP302CSAG
TBP303CSAG
TBP304CSAG
TBP305CSAG
TBP306CSAG
TBP307CSAG
TBP308CSAG
TBP309CSAG
TBP310CSAG
TBP311CSAG

3.81mm PITCH

Mant. Part No. &
anglia Order Code
Side Side
TBP302JSAG
TBP303JSAG
TBP304JSAG
TBP305JSAG
TBP306JSAG
201-1 000001101
TBP307JSAG
TBP308JSAG
TBP309JSAG
TBP310JSAG
TBP311JSAG
TBP312JSAG

Right Angle




3.5mm PITCH

Manf. Part No. & anglia Order Code	Ma ang
TBP302CHC	
TBP303CHC	
TBP304CHC	
TBP305CHC	
TBP306CHC	
TBP307CHC	
TBP308CHC	
ТВР309СНС	
△TBP310CHC	
TBP311CHC	

3.81mm PITCH

anf. Part No. & lia Order Code TBP302JHC TBP303JHC TBP304JHC TBP305JHC TBP306JHC TBP307JHC TBP308JHC TBP309JHC TBP310JHC TBP311JHC TBP312JHC

Straight (reversed body)



Wire entry on the rippled side of the plug.

3.5mm PITCH

Manf. Part No. & anglia Order Code

TBP312CSAG

TBP302CSBG TBP303CSBG TBP304CSBG TBP305CSBG TBP306CSBG TBP307CSBG TBP308CSBG TBP309CSBG TBP310CSBG TBP311CSBG TBP312CSBG

3,81mm PITCH

Manf. Part No. & anglia Order Code

TBP302JSBG TBP303JSBG TBP304JSBG TBP305JSBG TBP306JSBG TBP307JSBG TBP308JSBG TBP309JSBG TBP310JSBG TBP311JSBG TBP312JSBG



5mm PITCH

LUMBERG type KSC & KB

△ lumberg

A range of two part pluggable blocks, from 2 to 10 way, consisting of 5mm pitch pcb mounting socket headers and mating screw terminal plugs. Combines the convenience of screw connection with the ease of a plug & socket. Other ways are available to special order.

- · Two part pluggable blocks
- 5mm pitch, 10A rating
- · Polarised, latched mating
- Wire protection
- Choice of socket style
- Grey UL94V-2 flame retardant bodies





Specification

Body	. UL94V-2 PA6.6
Current rating [†]	. 10A
Voltage rating [†]	. 250Vac
Max. wire size	4.0mm ² (single)
E(U)	2.5mm ² (stranded)
	-25°C to +100°C

limited by pcb

Dimensions (mm)

WAYS	2	3	4	5	6	8	10
Length	10	15	20	25	30	40	507
Height (plugs)				17		. es	$U(\partial)_{\Pi_I}$
(vert. sockets)				13.2	Man.	M Goz	
(R/A sockets)		8.9					
Depth (plugs)	17						
(vert. sockets)	890						
(R/A sockets)	13.2						
Pin size (sockets)	0.7 x 1.1						
Pitch	5						

lumberg


For the very latest information and news on the full range of lumberg products available from Anglia, visit our website:

www.anglia.com/lumberg

Alternatively, contact our Sales Desk to discuss your specific requirements.

PLUGS – screw terminal

Fitted with wire protection guards.



Туре	Manf. Part No. & anglia Order Code
2 way	/ KSC2
3 way	KSC3
4 way	KSC4
5 way	KSC5
6 way	KSC6
8 way	KSC8
10 way	KSC10


SOCKET HEADERS - vertical



Type	Manf. Part No. & anglia Order Code
2 way	KB2
8\3 way	KB3
4 way	KB4
5 way	KB5
6 way 8 way	KB6 KB8
10 way	KB10

SOCKET HEADERS - right angle

Available with or without integral board grips



With Board Grips

KBW10

Туре	Manf. Part No. 8 a∩glia Order Cod
2 way	KBW2
3 way	KBW3
4 way	KBW4
5 way	KBW5
6 way	KBW6
8 way	KBW8

Without Board Grips

without board drips		
	Manf. Part No. &	
	anglia Order Code	
	KBWOO	
	KBWO2	
	KBW03	
	KBWO4	
	KBW05	
	KBW06	
	KBW08	
	KBWO10	

10 way

5mm PITCH

5.08mm PITCH

TAICOM type TBP3/A & K

TAiCOM

F11® 118

A range of two part pluggable blocks, from 2 to 12 way, offered in 5mm and 5.08mm pitch. Consisting of pcb mounting socket headers and mating, rising clamp screw terminal plugs, they combine the convenience of screw connection with the ease of a plug & socket. Other ways are available to special order.

- - 5mm Pitch
- **EXPANDED** RANGE 5.08mm Pitch

- Two part pluggable blocks
- 5mm & 5.08mm pitch, 15A rating
- Polarised, latched mating
- Rising clamp wire protection
- Combi screws
- Choice of plug & socket style
- Green UL94V-0 flame retardant bodies

Specification

Materials Mouldings Green glass filled polyamide to UL94V-0

Brass, tin plated M3 (R/A: M2.5), galvanised steel Screws

chromate finish Rising clamps Brass, tin plated

Ratings (limited by pcb) Current rating.....

300Vac Voltage rating


-33°C to +120°C (plugs) -40°C to +105°C (socket headers) Oper. temp. range


Wire Size

. 12 to 24awg 4.0mm² max. (solid) 2.5mm² max. (stranded) Range Metric capacity


Dimensions (mm)


PLUGS







straight





SOCKET HEADERS vertical







right angle

pitch (pitch x no. ways) +2.0

5mm PITCH

5.08mm PITCH

PLUGS - screw terminal

Choice of straight or right angle styles fitted with rising clamp type wire protection guards. Straight has option of reversed body.

Right Angle



Straight

Туре		
2	way	
3	way	
4	way	
5	way	
6	way	
7	way	
8	way	
9	way	
	way	
	way	
12	way	

Type

2 way

3 way

4 way

5 way

6 way

7 way

8 way

9 way

10 way

11 way

12 way

Type

2 way

3 way

4 way

5 way

6 way

7 way

8 way

9 way

10 way

11 way

12 way

5mm PITCH Manf. Part No. &

nglia Order Co
TBP302AG TBP303AG TBP305AG TBP305AG TBP306AG TBP307AG TBP308AG TBP309AG
TBP310AG TBP311AG TBP312AG

5.08mm PITCH Manf. Part No. &

iglia Order Cod
TBP302KG
TBP303KG
TBP304KG
TBP305KG
TBP306KG
TBP307KG
TBP308KG
TBP309KG
TBP310KG
TBP311KG
TBP312KG

Manf. Part No. &

TBP312ASAG

5mm PITCH

5.08mm PITCH

Manf. Part No. & anglia Order Code

TBP302HSAG TBP303HSAG TBP304HSAG TBP305HSAG TBP306HSAG TBP307HSAG TBP308HSAG TBP309HSAG TBP310HSAG TBP311HSAG TBP312HSAG

SOCKET HEADERS - pcb mounting

5mm PITCH

Manf. Part No. &

Manf. Part No. &

anglia Order Code

Choice of vertical or right angle styles each providing the option of closed end versions.

Vertical



Туре	anglia Order Co
2 way	TBP302AV
3 way	TBP303AV
4 way	TBP304AV
5 way	TBP305AV
6 way	TBP306AV
7 way	TBP307AV
8 way	TBP308AV
9 way	TBP309AV
0 way	TBP310AV
1 way	TBP311AV
2 way	TBP312AV

5 08mm PITCH Manf. Part No. &

anglia Order Code TBP302KV TBP303KV TBP304KV TBP305KV TBP306KV TBP307KV TBP308KV TBP309KV TBP310KV TBP311KV TBP312KV

Vertical (closed end)



end)	5mm PITCH
Туре	Manf. Part No. anglia Order Co
2 way	TBP302AVC

TBP303AVC 3 way 4 way TBP304AVC 5 way TBP305AVC TBP306AVC 6 way TBP307AVC 7 way 8 way TBP308AVC TBP309AVC 9 way TBP310AVC 10 way TBP311AVC 11 way 12 wav TBP312AVC

5.08mm PITCH

Manf. Part No. & anglia Order Code TBP302KVC TBP303KVC TBP304KVC TBP305KVC TBP306KVC TBP307KVC TBP308KVC TBP309KVC TBP310KVC TBP311KVC TBP312KVC

Straight (reversed body)



Wire entry on the

coding/smooth

side of the plug.

Wire entry on the rippled side of the plug

5mm PITCH

Manf. Part No. & anglia Order Code

TBP302ASBG TBP303ASBG TBP304ASBG TBP305ASBG TBP306ASBG TBP307ASBG TBP308ASBG TBP309ASBG TBP310ASBG TBP311ASBG TBP312ASBG

5.08mm PITCH

Manf. Part No. & a∩olia Order Code

TBP302HSBG TBP303HSBG TBP304HSBG TBP305HSBG TBP306HSBG TBP307HSBG TBP308HSBG TBP309HSBG TBP310HSBG TBP311HSBG TBP312HSBG

Right Angle



3 way 4 way 5 way 6 way 7 way 8 way 9 way 10 way 11 way

12 way

Туре

2 way

Manf. Part No. & anglia Order Code

TBP302AH TBP303AH TBP304AH TBP305AH TBP306AH TBP307AH TBP308AH TBP309AH TBP310AH TBP311AH

TBP312AH

5mm PITCH

5.08mm PITCH

Manf. Part No. & anglia Order Code TBP302KH **TBP303KH** TBP304KH

TBP305KH TBP306KH TBP307KH TBP308KH **TBP309KH** TBP310KH TBP311KH TBP312KH

Right Angle (closed end)



Type 2 way

3 way 4 way 5 way 6 way 7 way 8 way 9 way 10 way 11 way 12 way

5mm PITCH

Manf. Part No. & anglia Order Code TBP302AHC TBP303AHC TBP304AHC TBP305AHC TBP306AHC TBP307AHC TBP308AHC TBP309AHC TBP310AHC TBP311AHC TBP311KHC TBP312AHC TBP312KHC

5.08mm PITCH

Manf. Part No. & a∩glia Order Code TBP302KHC TBP303KHC TBP304KHC TBP305KHC TBP306KHC TBP307KHC TBP308KHC TBP309KHC TBP310KHC