

CONSTRUCTION/构造:		UL3265 26AWG	
CONSTRUCTION ITEM/结构项目		Units	A
CONDUCTOR 导体	CONSTRUCTION/构造	AWG	7/0.16±0.008
	MATERIAL/导体材质	---	Tinned Copper
	FILLER/填充	---	-----
	OD/绞合外径	mm	0.48
INSULATION 绝缘	MATERIAL/材质	---	XLPE
	OD/芯线外径	mm	1.1±0.10
	MIN.THICK/最小厚度	mm	0.20
	AVG.THICK/平均厚度	mm	0.26
	COLOR/颜色	---	black、brown、red、orange、yellow、green、blue、purple、gray、white
PACKAGING 包装	LENGTH/长度	M	610
	PAPER SKIN/纸箱	mm	****
MARKING 印字	E227566  AWM STYLE 3265 26AWG 125C 150V VW-1 ---  AWM I A/B 125C 150V FT1 WOER -LF-		

Characters/特性:

Electric Characters/电气性能:

1.Voltage rating/额定电压	150V
2.Temperature rating/温度等级	125°C
3.Spark test/火花测试	AC-1500V/1 sec MIN
4.Dielectric strength/耐压强度	AC-1500V/1 sec MIN
5.Conductor resistance/导体电阻	150Ω/KM MAXat20°C
6.Rock rest	---

CONSTRUCTION FIGURE/截面图:

