

Part Number: SL32 4R023

Ordering Different Lead Types:

| | |
|----------------------|---------------------------------------|
| Inside Kinked Leads | Not available |
| Outside Kinked Leads | Use -B after Ametherm's Part # |

For example: to order an outside kinked lead use part number SL32 4R023-B



| | |
|--|-------------------------------|
| Resistance @ 25°C | 4.0 Ω \pm 20% |
| Max Steady State Current Up to 65°C | 23.0 A |
| Max Recommended Energy Rating | 200.0 J |
| Actual Failure Point of Instantaneous Energy | 448.0 J |
| Resistance @ 100 % of Maximum Current | 0.020 Ω |
| Resistance @ 50% of Maximum Current | 0.065 Ω |
| Body Temperature at Maximum Current | 236 °C |
| Dissipation Constant | 65.4 mW/°C |
| Thermal Time Constant | 208 seconds |
| Material Type | "G" |
| Maximum Capacitance @ 240/440 VAC | 3400 μ F/ 1000 μ F |

| | |
|---------------------------------|-------------------|
| D | 30.0 \pm 2.5 mm |
| T | 6.35 \pm 0.4 mm |
| Lead Diameter | 1.3 \pm 0.1 mm |
| S | 7.8 \pm 2.0 mm |
| L | 38.0 \pm 9.0 mm |
| Coating Run Down Straight Leads | 5.0 \pm 1.0 mm |
| B | 7.8 mm Nom |
| C | 3.82 \pm 1.0 mm |

Revision Date April 26, 2005

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com