




EYELETS

EYELETS

Our GS Eyelets consists of various eyelets where the length and outside barrel diameters are graduated by 1/32". This grouping will meet the requirements of most general purpose eyeleting applications. Eyelets are most commonly requested in brass. Eyelets can also be made from steel, stainless steel, aluminum, and copper.

Eyelet Options

In addition to our Rolled Flange GS® Eyelets, GS® Eyelets can also be made with a flat flange, or with a closed end.



| Length Under Flange | 1/16 | 3/32 | 1/8 | 5/32 | 3/16 | 7/32 | 1/4 | 9/32 | 5/16 | 11/32 | 3/8 | 13/32 | 7/16 |
|------------------------|--------|--------|--------|--------|--------|--------|--------|--------|---------|---------|---------|---------|---------|
| Barrel Dia. 0.059 | | | | | | | | | | | | | |
| Flange Diameter 0.105 | GS2-2B | GS2-3B | GS2-4B | GS2-5B | GS2-6B | GS2-7B | — | — | — | — | — | — | — |
| *Metal Thickness 0.007 | | | | | | | | | | | | | |
| Barrel Diameter 0.089 | | | | | | | | | | | | | |
| Flange Diameter 0.150 | — | GS3-3B | GS3-4B | GS3-5B | GS3-6B | GS3-7B | GS3-8B | GS3-9B | GS3-10B | GS3-11B | GS3-12B | — | — |
| *Metal Thickness 0.009 | | | | | | | | | | | | | |
| Barrel Diameter 0.121 | | | | | | | | | | | | | |
| Flange Diameter 0.200 | — | GS4-3B | GS4-4B | GS4-5B | GS4-6B | GS4-7B | GS4-8B | GS4-9B | GS4-10B | GS4-11B | GS4-12B | — | — |
| *Metal Thickness 0.010 | | | | | | | | | | | | | |
| Barrel Diameter 0.152 | | | | | | | | | | | | | |
| Flange Diameter 0.245 | — | GS5-3B | GS5-4B | GS5-5B | GS5-6B | GS5-7B | GS5-8B | GS5-9B | GS5-10B | — | GS5-12B | — | — |
| *Metal Thickness 0.010 | | | | | | | | | | | | | |
| Barrel Diameter 0.183 | | | | | | | | | | | | | |
| Flange Diameter 0.290 | — | GS6-3B | GS6-4B | GS6-5B | GS6-6B | GS6-7B | GS6-8B | GS6-9B | GS6-10B | GS6-11B | GS6-12B | GS6-13B | GS6-14B |
| *Metal Thickness 0.011 | | | | | | | | | | | | | |
| Barrel Diameter 0.215 | | | | | | | | | | | | | |
| Flange Diameter 0.340 | — | GS7-3B | GS7-4B | GS7-5B | GS7-6B | GS7-7B | GS7-8B | GS7-9B | GS7-10B | GS7-11B | GS7-12B | GS7-13B | GS7-14B |
| *Metal Thickness 0.011 | | | | | | | | | | | | | |
| Barrel Diameter 0.246 | | | | | | | | | | | | | |
| Flange Diameter 0.385 | — | GS8-3B | GS8-4B | GS8-5B | GS8-6B | GS8-7B | GS8-8B | GS8-9B | GS8-10B | GS8-11B | GS8-12B | GS8-13B | GS8-14B |
| *Metal Thickness 0.011 | | | | | | | | | | | | | |