

PD Charger Wall Mount Series



Single Output 30W Data Sheet

For the latest revision, please visit power.liteon.com

Description

This specification defines the performance characteristics of single phase, 30 WATT, compatible USB-PD 3.0, 1 outputs power supply. This specification also defines worldwide safety and electromagnetic compatibility requirements for the power supply which is intended for use in IA products.

Features

- * Full AC input voltage range design.
- * Full Protections: Short-circuit/ Over-voltage/ Over-current/ Over temperature.
- * Less than 100mW low standby power.
- * IEC/EN 62368-1 design compliance.
- * Up to 5000 meters operating altitude.
- * AC plug is foldable.



Electrical Specification

Model Name	PA-1300-55HA					
Output						
Rated power	30W					
Rated voltage	5V	9V	12V	15V		3.3~16V
Rated current	3A	3A	2.5A	2A		3A
Ripple & Noise(max.) (note #1)	380mV					
Line & load regulation	±5%					
Hold-up time(min.)	5ms/115Vac					
Timing: AC ON delay / rising (max.)	5 sec / 275ms					
Input						
Rated voltage range	100~240Vac					
Operated voltage range	90~264Vac					
Current range (max.)	1.0A					
Power factor (typ.)	N/A					
Inrush current (typ.)	limited to a 29% margin of the I2t rating of fuse and bridge rectifier					
Frequency range	50-60Hz					
Leakage current (max.)	25uA at 250Vac					
Efficiency (typ.)	87.0%/30W					
Protection Function						

Over voltage (max.)	145% of rated voltage, latch-off protection
Over current (max.)	5.0A , latch-off protection
Short circuit at O/P	No damage, latch-off protection.
Over temperature	No damage, latch-off protection
Others	
MTBF (min.) (note#2)	100K hours @ rated load
Environment	
Temperature	(operating) 0~35°C / (storage) -20~85°C
Humidity	(operating) 10~95% RH non-condensing / (storage) 5~95% RH
Altitude (max.)	5000 meters
Mechanical	
Dimension	48(L)*48(W)*29mm(H)
Temperature rise of case (note #3)	ΔT less than 40°C
Weight (typ.)	160g
Safety	
Standard	IEC/EN 60950-1, K60950-1, IEC/EN 62368-1, CNS14336-1
Withstand voltage	Input-Output: 4242VDC
Isolation resistance(min.)	Input-Output: 30Mohm @ 500VDC, 25°C, 70%RH
EMC	
EN55032 (CISPR32)	Conducted EMI: class B / Radiated EMI: class B
FCC	Conducted EMI: class B / Radiated EMI: class B
EN61000-3-2	Harmonic distortion: The power less than 75W and no limit apply
EN61000-4-2	ESD: ±8KV contact discharge / ±15KV contact discharge
EN61000-4-3	Radiated RF immunity: 3V/m
EN61000-4-4	EFT: ±1KV (AC port)
EN61000-4-5	Surge: ±1KV DM / ±2KV CM
EN61000-4-6	Conducted RF immunity: 3V/m
EN61000-4-8	Magnetic field immunity: 1A/m
EN61000-4-11	Voltage dip immunity: Criteria B

Notes

#1: Ripple noise is measured with 0.47uF MLCC & 10uF low ESR capacitor.

#2: Input voltage is 115Vac and 230Vac, output is rated load at 25°C.

#3: 100Vac and rated load at 35°C ambient temperature.

Mechanical Specification

