



DΛ	NEI	CUT	OUT
			\ /\\/

REVISIONS							
REV.	DESCRIPTION	DATE	APPROVED				
А	INITIAL RELEASE	03/06/18	C.E.				



	inc	inches		
	Maxi	mini		
A	.198	.192		
В	.183	.177		



NOTES:

MATERIALS:

- INSULATORS = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B". LOCKWASHER = PHOSPHOR BRONZE PER ASTM B139, COPPER ALLOY C53400, TEMPER H04. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:

- CONTACT = GOLD PLATE PER ASTM B488-11, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER AMS-QQ-N-290.

 ALL OTHER METAL PARTS = NICKEL PLATE PER AMS-QQ-N-290, CLASS 1, GRADE G, EXCEPT 100 TO 200µin THICK OVER 50 TO 100µin THICK COPPER PER AMS 2418.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		C.E. 03/06/18		(This document canno communicated to a	third party wi		
		CHKD: DATE	a RADIALL companywritten permission of RADIALL.					
DECIMAL	ANGLE	D.N. 03/06/18	8 SMB STRAIGHT MALE JACK					
		APVD: DATE	T BULKHEAD MOUNT					
		J.M. 03/06/18	SOLDER POT RECEPTACLE					
REFERENCE: MATERIA		MATERIALS & FINISHES:	SIZE A	FSCM NO. 19505	DWG NO. 2004-	-7511	-000	REV A
ORIGINATED: C.E.		SEE NOTES		19303	2001	/ 0 1 1	000	\Box
DATE: 03/06/18		SEE NOTES	SCALE	6:1	THIRD ANGLE (⊕ 🖂	SHEET 1 O	F 1