



File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	29.0	±	Max
	T:	7.8	±	Max
	Lead Diameter		±	
	S:	17.5	±	Nom
	L:	22.0	±	Nom
Coating Lead Run Down (straight Leads)		5.0	±	Max
	B:	4.80	±	Nom
	C:	0.90	±	Nom



Electrical Specifications

	Resistance:	0.5	Ω	±	25 %
Max Steady State Current upto 65°C:		30.00		A	
Max Rec. Energy Rating:		30		J	
Actual Failure Instantaneous Energy:		600		J	
Maximum Capacitance @ 120 VAC:		20,700		μf	
Maximum Capacitance @ 240 VAC:		5,200		μf	
Maximum Capacitance @ 440 VAC:		1,300		μf	
Maximum Capacitance @ 680 VAC:		640		μf	
Resistance @ 100% Max Current:		0.01		Ω	
Resistance @ 50% Max Current:		0.03		Ω	
Body Temperature at 100% Max Current:		183.00		°c	
Dissipation Constant:		78.2		mw/°c	
Thermal Time Constant:		55		Sec.	
Material Type (for Beta and Curve):		B			

AS32 0R536-100	
Date: 02/14/2012	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: