




File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	30.0	± Max
	T:	7.8	± Max
	Lead Diameter		±
	S:	17.1	± Nom
	L:	21.0	± Nom
	Coating Lead Run Down (straight Leads)	5.5	± Max
	B:	4.80	± Nom
	C:	0.80	± Nom



Electrical Specifications

	Resistance:	2.0	Ω	± 25 %
	Max Steady State Current upto 65°C:	25.00		A
	Max Rec. Energy Rating:	300		J
	Actual Failure Instantaneous Energy:	600		J
	Maximum Capacitance @ 120 VAC:	20,700		µf
	Maximum Capacitance @ 240 VAC:	5,200		µf
	Maximum Capacitance @ 440 VAC:	1,300		µf
	Maximum Capacitance @ 680 VAC:	640		µf
	Resistance @ 100% Max Current:	0.02		Ω
	Resistance @ 50% Max Current:	0.04		Ω
	Body Temperature at 100% Max Current:	220.00		°c
	Dissipation Constant:	78.2		mw/°c
	Thermal Time Constant:	55		Sec.
	Material Type (for Beta and Curve):	B		

AS32 2R025	
Date: 03/15/2011	Drawn by: Erin Landis
Ametherm, Inc. 961 Fairview Drive Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A