

# General Purpose Thick Film Resistors (CR Series)



## Features:

- RoHS Compliant (5/6) and Halogen Free
- TCR as low as  $\pm 100\text{ppm}$
- Available Sizes 01005 to 2512
- Stable over temperature range
- Good power dissipation capabilities (Rated power is conservatively rated)
- 100% matte Tin over Nickel with wrap around termination for excellent solderability
- Some values available for conductive epoxy application (suitable for MRI applications)

## Part Number Structure

CR Series	1206 Size	8W Power Rating	103 Resistance	J Tolerance	Termination	T Packaging	Optional Reel Identifier						
	01005 0201 0402 0603 0805 1206 1210 2010 2512	32W = 0.031W 20W = 0.05W 16W = 0.063W 10W = 0.10W 8W = 0.125W 4W = 0.25W 2W = 0.50W 1W = 1W 2W = 2W	<table border="1"> <tr> <td>3 DIGIT (J TOL.)</td> <td>2R2=2.2Ω 103=10KΩ</td> </tr> <tr> <td>4 DIGIT (D &amp; F TOL.)</td> <td>10R2=10.2Ω 1002=10KΩ</td> </tr> <tr> <td>Jumper</td> <td>3 zeros</td> </tr> </table> <p>Note: 1% E24 values may be marked with a 3 digit code.</p>	3 DIGIT (J TOL.)	2R2=2.2Ω 103=10KΩ	4 DIGIT (D & F TOL.)	10R2=10.2Ω 1002=10KΩ	Jumper	3 zeros	D = $\pm 0.5\%$ F = $\pm 1\%$ J = $\pm 5\%$  No tolerance specified for the zero ohm  Leave blank for zero ohm value	Leave blank for standard termination.  P = Palladium Silver Termination (PdAg)	T = Tape & Reel	Leave blank if standard Reel size.  Add "-13" if 13" Reel is required
3 DIGIT (J TOL.)	2R2=2.2Ω 103=10KΩ												
4 DIGIT (D & F TOL.)	10R2=10.2Ω 1002=10KΩ												
Jumper	3 zeros												

**Example P/N:** CR1206-8W-103JT

Standard termination finish is 100% matte Tin (Sn) over Nickel.

## Dimensions

Size	L	W	T	C <sub>1</sub>	C <sub>2</sub>
01005	0.016 ± 0.0008 (0.4 ± 0.02)	0.008 ± 0.0008 (0.2 ± 0.02)	0.005 ± 0.0008 (0.13 ± 0.02)	0.003 ± 0.001 (0.08 ± 0.03)	0.003 ± 0.001 (0.08 ± 0.03)
0201	0.024 ± 0.002 (0.6 ± 0.05)	0.012 ± 0.001 (0.3 ± 0.02)	0.010 ± 0.002 (0.25 ± 0.05)	0.020 ± 0.008 (0.50 ± 0.20)	0.006 ± 0.002 (0.15 ± 0.05)
0402	0.040 ± 0.002 (1.0 ± 0.05)	0.020 ± 0.001 (0.5 ± 0.02)	0.014 ± 0.002 (0.35 ± .05)	0.008 ± 0.004 (0.2 ± 0.1)	0.008 ± 0.004 (0.2 ± 0.1)
0603	0.063 ± 0.004 (1.6 ± 0.1)	0.031 ± 0.004 (0.8 ± 0.1)	0.018 ± 0.004 (0.45 ± 0.1)	0.012 ± 0.006 (0.30 ± 0.15)	0.012 ± 0.006 (0.30 ± 0.15)
0805	0.079 ± 0.006 (2.0 ± 0.15)	0.050 ± 0.006 (1.25 ± 0.15)	0.018 ± 0.006 (0.45 ± 0.15)	0.014 ± 0.006 (0.35 ± 0.15)	0.014 ± 0.006 (0.35 ± 0.15)
1206	0.126 ± 0.006 (3.2 ± 0.15)	0.063 ± 0.006 (1.6 ± 0.15)	0.022 ± 0.006 (0.56 ± 0.15)	0.020 ± 0.008 (0.50 ± 0.20)	0.020 ± 0.008 (0.50 ± 0.20)
1210	0.126 ± 0.006 (3.2 ± 0.15)	0.098 ± 0.006 (2.50 ± 0.15)	0.022 ± 0.006 (0.56 ± 0.15)	0.020 ± 0.008 (0.50 ± 0.20)	0.020 ± 0.008 (0.50 ± 0.20)
2010	0.197 ± 0.006 (5.0 ± 0.15)	0.098 ± 0.006 (2.50 ± 0.15)	0.022 ± 0.006 (0.56 ± 0.15)	0.026 ± 0.008 (0.65 ± 0.25)	0.024 ± 0.008 (0.60 ± 0.20)
2512 (1W)	0.248 ± 0.006 (6.3 ± 0.15)	0.126 ± 0.006 (3.2 ± 0.15)	0.022 ± 0.006 (0.56 ± 0.15)	0.026 ± 0.008 (0.65 ± 0.25)	0.024 ± 0.008 (0.60 ± 0.20)
2512 (2W)	0.248 ± 0.006 (6.3 ± 0.15)	0.126 ± 0.006 (3.2 ± 0.15)	0.024 ± 0.008 (0.60 ± 0.20)	0.024 ± 0.008 (0.60 ± 0.20)	0.020 ± 0.008 (0.50 ± 0.20)

Unit: inches (mm)

## Structure

1	Alumina Substrate	6	Tin Plating
2	Backside Electrode	7	Primary Coating
3	Topside Electrode	8	Secondary Layer
4	Edge Electrode	9	Resistive layer
5	Nickel Plating	10	Marking


# General Purpose Thick Film Resistors (CR Series)

## Electrical Specifications and Range

Size		01005	0201	0402		0603		0805		1206		1210		2010		2512	
Power Rating at 70°C (W)		0.03W (1/32W)	0.05W (1/20W)	0.063W (1/16W)	0.10W (1/10W)	0.063W (1/16W)	0.10W (1/10W)	0.10W (1/10W)	0.125W (1/8W)	0.125W (1/8W)	0.25W (1/4W)	0.50W (1/2W)	0.50W (1/2W)	1.0W	1.0W	1.0W	2.0W
Max. Working Voltage		$\sqrt{PR}$ or 15V whichever is less	$\sqrt{PR}$ or 25V whichever is less	$\sqrt{PR}$ or 50V whichever is less	$\sqrt{PR}$ or 75V whichever is less	$\sqrt{PR}$ or 150V whichever is less	$\sqrt{PR}$ or 150V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less	$\sqrt{PR}$ or 200V whichever is less
Operating Temp. Range		-55°C to +125°C	-55°C to +125°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C	-55°C to +155°C
Zero Ohm (Jumper)	Current Rating	0.5A	0.5A	1A	1A	2A	2A	2A	2A	2A	2A	2.5A	3.5A	3.5A	4A	4A	4A
Zero Ohm (Jumper)	Resistance	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)	50 mΩ (max)
Tolerance	TCR	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range	Resistance Range
±0.5% (D)	±100ppm	-	-	10Ω - 1MΩ	-	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	-	-	-	-	-	-	-
	±200ppm	-	-	1.02MΩ - 10MΩ	-	1.02MΩ - 10MΩ	1.02MΩ - 10MΩ	1.02MΩ - 10MΩ	1.02MΩ - 10MΩ	-	-	-	-	-	-	-	-
±1% (F)	±100ppm	-	-	10Ω - 10MΩ	10Ω - 1MΩ	10Ω - 10MΩ	10Ω - 10MΩ	10Ω - 10MΩ	10Ω - 10MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ	10Ω - 1MΩ
	±200ppm	-	10Ω - 10MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 10MΩ	1Ω - 9.76Ω; 10.2MΩ - 21.5MΩ	1Ω - 9.76Ω; 10.2MΩ - 21.5MΩ	1Ω - 9.76Ω; 10.2MΩ - 21.5MΩ	1Ω - 9.76Ω; 10.2MΩ - 21.5MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ	1Ω - 9.76Ω; 10.2MΩ - 20MΩ
	±250ppm	100Ω - 1MΩ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	±300ppm	10Ω - 99Ω	-	-	-	-	-	-	-	20.5MΩ - 21.5MΩ	-	20.5MΩ - 21.5MΩ	-	-	-	-	-
±5% (J)	±100ppm	-	-	-	-	-	-	-	-	10Ω - 1MΩ	-	10Ω - 1MΩ	-	10Ω - 1MΩ	-	10Ω - 1MΩ	-
	±200ppm	-	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 10MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ	1Ω - 9.76Ω; 1.02MΩ - 20MΩ
	±250ppm	100Ω - 1MΩ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	±300ppm	10Ω - 99Ω	-	-	-	-	-	-	-	20.5MΩ - 21.5MΩ	-	20.5MΩ - 21.5MΩ	-	-	-	-	-
	±350ppm	-	-	-	-	10MΩ - 22MΩ	10MΩ - 22MΩ	10MΩ - 22MΩ	10MΩ - 22MΩ	-	-	-	-	-	-	-	-


NOTE: Overload Voltage=2.5\* $\sqrt{P \cdot R}$ .

## Marking Code




- 1% E-24 values for 0603 size and larger are typically marked with the standard 3 digit marking code.
- 1% E-96 values for 0805 size and larger may or may not be marked with the standard 4 digit marking code.
- 5% E-24 values for 0603 size and larger, will be marked with standard 3 digit marking code.
- 0603 -1% E-96 values will be marked with a standard 3 digit alpha numeric code (Please see page 61 for alpha numeric codes).
- 01005, 0201 and 0402 cannot be marked.
- 5% E-24 values for 1210-2512, may be marked with 4 digit marking code.
- E-192 values will not typically be marked.

## Derating Curve



# General Purpose Thick Film Resistors (CR Series)

## Reel Specifications




Unit: mm (inch)

C	E	F	G	H	M
13.0 ± 0.2 (0.51 ± 0.008)	60.0 ± 1.0 (2.36 ± 0.03)	11.4 ± 1.0 (0.45 ± 0.04)	9.0 ± .3 (0.35 ± 0.012)	1.5 ± .3 (0.06 ± 0.012)	180 ± 2.0 (7.09 ± 0.08)

Minimum of 30 empty pockets at the beginning of reel, 65 minimum empty pockets at the end.


## Tape Specifications



All dimensions in mm.

Tape	Size (inches)	A	B	W	E	F	T	G	H	J	Dø
Paper	01005	0.45 ± 0.03	0.25 ± 0.03	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.40 ± 0.10	2.0 ± 0.05	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	0201	0.7 ± 0.08	0.4 ± 0.08	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.42 ± 0.20	2.0 ± 0.05	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	0402	1.15 ± 0.1	0.65 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.45 ± 0.10	2.0 ± 0.05	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	0603	1.9 ± 0.1	1.1 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.70 ± 0.10	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	0805	2.4 ± 0.1	1.65 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.85 ± 0.10	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	1206	3.5 ± 0.1	1.9 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.85 ± 0.10	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	1210	3.5 ± 0.1	2.8 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	0.85 ± 0.10	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
Embossed	2010	5.4 ± 0.2	2.9 ± 0.2	12.0 ± 0.1	1.75 ± 0.1	5.5 ± 0.5	1.2	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0
	2512	6.9 ± 0.2	3.6 ± 0.2	12.0 ± 0.1	1.75 ± 0.1	5.5 ± 0.5	1.2	8.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.5 + 0.1-0

## Peel Back Force and Direction Diagram



Peel back force and direction of peel back angle should follow EIA481-1-A. Peel back force should be between 0.1N – 1.3N and peel back angle of 165° – 180°.