

Ordering Code:


CP35 ** P * V S 0 - NH
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No.
- ② No. of Circuits: 02~24
- ③ Contact type: P= Plug
- ④ Contact plated:
 - 1= Matte Tin Plated over Nickel
 - A= Selective Gold Flash Plated over 1.27 μm(50 μ") Nickel
 - B= Selective 0.38 μm(15 μ") Gold Plated over 1.27 μm(50 μ") Nickel
 - C= Selective 0.76 μm(30 μ") Gold Plated over 1.27 μm(50 μ") Nickel
- ⑤ V= Straight
- ⑥ Mount type : S= SMT Type
- ⑦ Other options: 0= With metal board lock (Standard)
- ⑧ -NH= For Lead Free IR Reflow Processes and Halogen-Free

Lead Free Process

Halogen-Free

RoHS compliant

④						UNIT: mm / inch	TITLE: 3.00mm PITCH STRAIGHT SMT TYPE POWER CONN.	 瀚荃股份有限公司 CviLux Corporation	DRAWING NO.	CP35213SA	PART NO.	CP35**P*VS0-NH
③						TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:		SCALE	3 / 1	SHEET	2 OF 2
②						.X ± 0.30/.012 X' ± 1'	FINISH:					
①						.XX ± 0.20/.008 .X' ±						
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Eisley	7/04-17'	.XXX ± 0.10/.004 .XX' ±					

