

Category	Series	Appearance	Features	No. of poles	Seal Tape	RoHS Compliant	Lead-Free Solderable
DIP SWITCH	DS, DP, DA		Slide/Piano/Right Angle	2-10, 12	-	•	•
	DM, DJ, DL, NDI		SMT/IC type	1-10, 12	•	•	•
	EI, EM		End Stackable	2, 3, 4, 6, 8, 10	•	•	•
	EPI, EPM		Piano type End Stackable	4, 8	-	•	•
	TDS		Tri-State	4, 8, 9, 10	-	•	•
	TII, TIM		Tri-State Low Profile type	4, 6, 8, 9, 10	•	•	•
	SIP		Single in Line	2, 4, 6, 8, 10	-	•	•
	HDS		Half Pitch (H: 2.3 mm)	8	•	•	•
	FHDS, NHDS		Half Pitch (H: 1.6 mm)	2, 4, 6, 8, 10	•	•	•
	RH, RV, RM		Rotary	10, 16	•	•	Except RM
Category	Series	Appearance	Features	Dimensions mm	Earth Terminal	RoHS Compliant	Lead-Free Solderable
TACT SWITCH	DTS-6, DTS-2		Thru Hole type	6.2x6.2 12.0x12.0	-	•	•
	DTSM-6, DTSM-2		SMT type	6.2x6.2 12.0x12.0	-	•	•
	DTSA-6		Right Angel type	6.55x7.4	-	•	•
	DTSG-6, DTSG(P)-2		Ground Terminal type	6.2x6.2 12.0x12.0	•	•	•
	DTSU-6		Multiple	6.2x6.2	-	•	•
	DTST-6		Radial Taping type	6.2x6.2	-	•	•
	DTSHW-6, DTSMW-2		Washable	6.2x6.3	DTSMW-66 only	•	•
	DTSJW-6		Washable	6.2x6.3	•	•	•
	DTS(G)L-6, DTS(G)F-6		Thinner type Pitch 4.0 mm	6.2x6.4	•	•	•
	DTS(G)ZM-6 DTSYH-6		Thinner type Pitch 4.5 mm	6.2x6.2	•	•	•
	TA(S)-6		SMT in Right Angle	6.1x4.6	-	•	•
	DTS-3, DTSM(L)-3		Thru Hole SMT	3.5x6.0	-	•	•
	TMG-3		Thinner type (H:2.5 mm)	3.7x6.0	•	•	•
	TAC-3, TA(N)2-3		Side-Push	4.0x7.3 4.6x7.0	-	•	•
	1188		Slide-Push	3.5x7.0	-	•	•
TMG-5, TJG-5		Miniature type	5.2x5.2	•	•	•	



Category	Series	Appearance	Features	Dimensions mm	Earth Terminal	RoHS Compliant	Lead-Free Solderable
TACT SWITCH	PT		Side-Push	3.5x4.7	•	•	•
	MPT		Side-Push Vertical-Push	2.9x3.9	•	•	•
CAP	KTSC-6, KTSC-2		For 6x6, 12x12 Tact Switch	Round/Square	–	•	–
	KTL-RA, KTL-SA		For TLL-6 series	Round/Square	–	•	–
Category	Series	Appearance	Poles-Positions	No. of poles	Travel	RoHS Compliant	Lead-Free Solderable
SLIDE SWITCH	SS		1-2, 1-3	1	2 mm	•	•
	MSS		1-2, 1-3, 1-4, 2-2	1, 2	1.5 mm	•	•
	LSS		1-2, 2-2	1, 2	2 mm	•	•
Category	Series	Appearance	Operations type	Soldering	Operation Force	RoHS Compliant	Lead-Free Solderable
DETECTOR SWITCH	TE		Vertical	Thru Hole/SMT	30gf max	•	•
	TE-MR		Horizontal	SMT	40gf max	•	–
	ATE		Vertical	SMT	40gf max	•	•
	BTE		Vertical	SMT	50gf max	•	•
	CTE		Vertical	SMT	35gf max	•	–
	FTE		Horizontal	SMT	50gf max	•	•
	TU		Vertical	SMT	40gf max	•	•
	LF		Vertical	–	100gf max	•	•
Category	Series	Appearance	Function	Dimensions mm	Reflow Soldering	RoHS Compliant	Lead-Free Solderable
MULTI FUNCTION SWITCH	MT4 MT5		4-direction (+ Center Push)	7.7x7.4	•	•	•
	TT5		5-direction Operated	9.3x9.3	•	•	•
	2A		Double Action	6.4x6.4	•	•	•
	M2A		Double Action	6.0x6.0	•	•	•
	TL(L)-6		LED type	6.1x6.1	–	•	•
	TML-3		LED type	6.8x4.1	•	•	–
	PL		Push & Lever	11.3x9.3	•	•	–
	PL3		Push & Lever	11.8x11.8	•	•	•
	SRM		8-way Direction	11x11.5	•	•	•