

64K CMOS Static RAM (8192×8) 28PIN 6264

型名	社名	温度範囲 (°C)	スイッチング特性										電源				入力 [*typ]				出力 [*typ]		備考
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWR max (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (1SB/1SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/VIOL max (V/mA)	VOH/VOH min (V/mA)	Co max (pF)		
LC3664R/LR-10	SANYO	0~70	100	100	5	10	35	70	50	0	0	0	4.5~5.5	35	3/0.1	0.8	2.2	6*	0.4/2.0	2.4/1.0	5*		
LC3664RM/RML-10	SANYO	0~70	100	100	5	10	35	70	50	0	0	10	4.5~5.5	35	3/1	0.8	2.2	6*	0.4/2.0	2.4/1.0	5*		
LC3664RS/RSL-10	SANYO	0~70	100	100	5	10	35	70	50	0	0	10	4.5~5.5	35	3/1	0.8	2.2	6*	0.4/2.0	2.4/1.0	5*		
LC3664BL-70	SANYO	0~70	70	70	10	20	30	50	30	0	0	0	4.5~5.5	10	2/0.006	0.8	2.2	6	0.4/2.1	2.4/1	8		
LC3664BL-85	SANYO	0~70	85	85	10	20	30	50	30	0	0	0	4.5~5.5	10	2/0.006	0.8	2.2	6	0.4/2.1	2.4/1	8		
LC3664BL-10	SANYO	0~70	100	100	10	20	30	60	35	0	0	0	4.5~5.5	10	2/0.006	0.8	2.2	6	0.4/2.1	2.4/1	8		
LC3664BL-12	SANYO	0~70	120	120	10	20	30	70	40	0	0	0	4.5~5.5	10	2/0.006	0.8	2.2	6	0.4/2.1	2.4/1	8		
LH5160/D/N-10L	SHARP	0~70	100	100	40	10	20	50	20	15	10	15	4.5~5.5	40	10/0.001	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5160H-10L	SHARP	-40~85	100	100	40	10	20	50	25	20	15	20	4.5~5.5	40	10/0.003	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5164-10	SHARP	0~70	100		40	10	30	50	25	20	15		4.5~5.5	40	10/-	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5164-12	SHARP	0~70	120		50	10	30	60	30	20	15		4.5~5.5	40	10/-	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5164-15	SHARP	0~70	150		50	10	30	60	30	20	15		4.5~5.5	40	10/-	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5164D/N-10L	SHARP	0~70	100	100	40	10	20	50	25	20	15	20	4.5~5.5	40	10/0.001	0.8	2.2	7	0.4/2.1	2.4/1.0	10		
LH5164L-10	SHARP	0~70	100	100	40	20	30	50	30	20	15	20	4.5~5.5	40	10/0.001	0.8	2.2	7	0.4/4	2.4/2.3	10		
LH5164L-12	SHARP	0~70	120	120	50	20	30	60	30	20	15	20	4.5~5.5	40	10/0.001	0.8	2.2	7	0.4/4	2.4/2.3	10		
LH5164L-15	SHARP	0~70	150	150	50	20	30	60	30	20	15	20	4.5~5.5	40	10/0.001	0.8	2.2	7	0.4/4	2.4/2.3	10		
LH5168/D/N-10L	SHARP	-10~70	100	100	40	10	20	60	40	0	0	0	4.5~5.5	45	10/0.001	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5168H/HD/HN-10L	SHARP	-40~85	100	100	40	10	20	60	40	0	0	0	4.5~5.5	50	10/0.003	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5168SH	SHARP	-40~85	500	500	100	20	40	150	100	0	100	50	2.5~5.5	50	10/0.003	0.2	2.3	7	0.5/0.4	2.0/0.4	10		
LH5168-80L	SHARP	-10~70	80	80	40	10	20	60	40	0	0	0	4.5~5.5	55	5/0.001	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5268A-70LL	SHARP	-10~70	70	70	35	10	30	40	30	0	0	0	4.5~5.5	50	3/0.04	0.8	2.2	7	0.4/2.1	2.4/1	10		
LH5268A-10LL	SHARP	-10~70	100	100	40	10	30	60	40	0	0	0	4.5~5.5	40	3/0.04	0.8	2.2	7	0.4/2.1	2.4/1	10		
MSM5165FP-10	mitsubishi		100		50	35	35	60	35	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-10L	mitsubishi		100		50	35	35	60	35	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-12	mitsubishi		120		60	40	40	70	40	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-12L	mitsubishi		120		60	40	40	70	40	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-15	mitsubishi		150		70	50	50	100	60	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-15L	mitsubishi		150		70	50	50	100	60	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-70	mitsubishi		70		35	30	30	40	30	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165FP-70L	mitsubishi		70		35	30	30	40	30	5	0		4.5~5.5	45	3/-	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-10	mitsubishi	0~70	100		50	20	35	60	35	5	0		4.5~5.5	50	3/2	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-10L	mitsubishi	0~70	100		50	20	35	60	35	5	0		4.5~5.5	50	3/0.1	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-12	mitsubishi	0~70	120		60	20	40	70	40	5	0		4.5~5.5	50	3/2	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-12L	mitsubishi	0~70	120		60	20	40	70	40	5	0		4.5~5.5	50	3/0.1	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-70	mitsubishi	0~70	70		35	20	30	40	30	5	0		4.5~5.5	50	3/2	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5165P-70L	mitsubishi	0~70	70		35	20	30	40	30	5	0		4.5~5.5	50	3/0.1	0.8	2.2	6	0.4/2	2.4/1	8		
MSM5178P-35	mitsubishi		35		20	20	20	20	17	0	0		4.5~5.5	120	2/-	0.8	2.2	6	0.4/0.8	2.4/4	8		
MSM5178P-45	mitsubishi		45		25	25	25	25	20	0	0		4.5~5.5	120	2/-	0.8	2.2	6	0.4/0.8	2.4/4	8		
MSM5178P-55	mitsubishi		55		35	35	35	35	30	0	0		4.5~5.5	120	2/-	0.8	2.2	6	0.4/0.8	2.4/4	8		
MB81C78-45	FUJITSU		45		20	5	25	25	20	0	5		4.5~5.5	120	15/-	0.8	2.2	7	0.4/8	2.4/4	8		
MB81C78-55	FUJITSU		55		25	5	30	30	30	0	5		4.5~5.5	120	15/-	0.8	2.2	7	0.4/8	2.4/4	8		
MB81C78A-35	FUJITSU	0~70	35	35	15	3	20	20	17	0	0	3	4.5~5.5	90	25/15	0.8	2.2	7	0.4/0.2	2.4/4.0	8 3		