



Manufactured by Stern Engineering  
 P/N 07225225  
 -Power supply 0-24V AC/DC  
 -Switch voltage 0-24V AC peak/DC  
 -Switch current Max 1A  
 -Green illuminated 24V AC/DC

**Green LED**

manufactured on: Date CE RoHS

- NOTES:**
1. Material: AISI 303
  2. Rated Voltage: (0-24 V AC/DC)  
 Rated Current: max 1A  
 Switch Resistance "On": (<1 Ohms )  
 Switch Resistance "Off": (> 5 Megaohms )  
 Switch Capacitance : (100pF)  
 Overvoltage protection 34 V DC  
 Impulse Time : 300 mSEC  
 Actuation Force Typically : (3-5 N )  
 Climate data: -40C to +85C per MIL STD 810G  
 Operating cycle : (>10 million )
  3. Green illuminated 24V AC/DC
  4. IP protection: IP68 per IEC 60529; IP69K per DIN 40050-9
  5. Mechanical shock : 75g per MIL STD 810G
  6. Vibration: 5-500Hz/9.4m/s<sup>2</sup> per IEC 60721
  7. Potting: Epoxy Resin Silicone Free

Pinfect:27/05/2013 (sashok)

All Dimensions in: mm		Code:	<small>THIS DRAWING IS VALID FOR THE DATE INDICATED ONLY AND NOT BE USED EXCEPT IN CONNECTION WITH THE SPECIFICATION OF WHICH IT IS A PART OR IN CONNECTION WITH ANY OTHER USE.</small>	<small>TOLERANCES UNLESS OTHERWISE SPECIFIED:          XX ± 0.1          X ± 0.2          .X ± 0.5          ANG ± 15%</small>	Scale 2:1	Weight
Material					Description	
Engineer: _____ Draftsman: Nataly Checked: Gabriel Approval: _____			Name: _____ Date: 06.11.12 06.11.12		Material: _____ Description: <b>BPSSN19PGFG0</b>	
No	ECO	Description	Name	Date	Cat. no <b>07225225</b>	
Finish			<b>IBS ELECTRONICS</b>		Revision Drawing no. <b>00 P95-00.00.00</b>	
Next Assy					Sheet 1 of 1 <b>A3</b>	