



Manufactured by Stern Engineering
 P/N 07225235
 -Rated voltage 0-24 V AC/DC
 -Switch current 1A
 -Switch pulse time up to: 300 msec

manufactured on: Date CE RoHS

- NOTES:**
1. Material: AISI 303.
 2. Rated Voltage: (0-24 V AC/DC)
 Rated Current: max 1A
 Switch Resistance "On" : (<1 Ohms)
 Switch Resistance "Off" : (> 5 Megaohms)
 Switch Capacitance : (100pF)
 Impulse Time : 300 mSEC
 Actuation Force Typically : (3-5 N)
 Climate data: -40C to +85C per MIL STD 810G
 Operating cycle : (>10 million)
 3. IP protection: IP68 per IEC 60529; IP69K per DIN 40050-9.
 4. Mechanical shock : 75g per MIL STD 810G.
 5. Vibration: 5-500Hz/9.4m/s² per IEC 60721.
 6. Potting: Epoxy Resin Silicone Free.



All Dimensions in: mm		Code:		THIS DRAWING IS VALID FOR THE PARTS LISTED ONLY. ANY OTHER PARTS LISTED ARE NOT COVERED BY THIS DRAWING. ALL RIGHTS RESERVED.	TOLERANCES UNLESS OTHERWISE SPECIFIED XXX ± 0.1 X ± 0.2 X ± 0.5 ANG ± 1.5%	Scale	Weight
						Material	Description
				Engineer	Name	Date	BPSSN12PNFK3
				Draftsman	Sasha	25.02.13	
				Checked			Cat.no 07225235
				Approval	Gabriel	25.02.13	
No	ECO	Description	Name	Date	Revision Drawing no.		
					01	P24-06.00.00	Sheet 1 of 1 A3
Next assy		Finish		IBS ELECTRONICS			