

## Lower Voltage Ceramic Singlelayer DC Disc Capacitors 2 kV<sub>DC</sub> to 7.5 kV<sub>DC</sub>


**FEATURES**

- Low losses
- High capacitance in small sizes
- High stability
- Radial leads
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

**APPLICATIONS**

- Lighting ballasts
- SMPS
- DC and pulse high voltage

**DESIGN**

The capacitors consist of a ceramic disc of which both sides are silver-plated. Connection leads are made of tinned copper having diameters of 0.025" (0.64 mm) or 0.032" (0.81 mm).

The capacitors may be supplied with radial kinked or straight leads having lead spacing of 0.250" (6.35 mm) or 0.375" (9.5 mm) or 0.500" (12.7 mm).

The standard tolerances are ± 10 % or ± 20 %.

Coating is made of resin coating or flame retardant epoxy resin in accordance with "UL 94 V-0".

QUICK REFERENCE DATA						
DESCRIPTION	VALUE					
Ceramic Class	1		2			
Ceramic Dielectric	U2J, R3L	C0G, U2J, R3L	X7R, Y5S, Y5U, Z5U, Y5V	X7R, Y5S, Y5U, Z5U, Y5V	X5F, X5S, Y5U, Z5U	X5F, Y5U, Z5U
Voltage (V <sub>DC</sub> )	3000	6000	2000	3000	6000	7500
Min. Capacitance (pF)	10	10	100	47	100	100
Max. Capacitance (pF)	33	47	100 000	33 000	10 000	2500
Mounting	Radial					

**INSULATION RESISTANCE**

2 kV <sub>DC</sub>	min. 10 000 MΩ
3 kV <sub>DC</sub>	min. 50 000 MΩ
6 kV <sub>DC</sub>	min. 75 000 MΩ
7.5 kV <sub>DC</sub>	min. 200 000 MΩ

**TOLERANCE ON CAPACITANCE**

± 10 %, ± 20 %, - 20 % to + 80 %

**DISSIPATION FACTOR**

0.2 % max. at 1 MHz; 1 V  
2.0 % max. at 1 kHz; 1 V

**CATEGORY TEMPERATURE RANGE**

- 25 °C to + 85 °C

**CLIMATIC CATEGORY ACC. TO EN 60068-1**

25/085/21

**OPERATING TEMPERATURE RANGE**

- 25 °C to + 105 °C

**CAPACITANCE RANGE**

10 pF to 0.10 μF

**RATED VOLTAGE**

2 kV<sub>DC</sub>  
3 kV<sub>DC</sub>  
6 kV<sub>DC</sub>  
7.5 kV<sub>DC</sub>


**DIELECTRIC STRENGTH BETWEEN LEADS**

Component test:

2 kV <sub>DC</sub>	3500 V <sub>DC</sub> , 2 s
3 kV <sub>DC</sub>	5000 V <sub>DC</sub> , 2 s
6 kV <sub>DC</sub>	10 500 V <sub>DC</sub> , 2 s
7.5 kV <sub>DC</sub>	11 250 V <sub>DC</sub> , 2 s

**CERAMIC DIELECTRIC**

C0G, U2J, R3L (Class 1)  
X7R, X5F, X5S, Y5S, Y5U, Y5V, Z5U (Class 2)



<b>ORDERING INFORMATION, CERAMIC 2 kV<sub>DC</sub></b>											
C (pF)	TOL. (%)	D <sub>max.</sub> DIAMETER INCH (mm)	T <sub>max.</sub> THICKNESS INCH (mm)	LS LEAD SPACE INCH (mm)	WIRE SIZE		ORDERING CODE				
					AWG	INCH (mm)					
<b>X7R</b>											
100	± 10	0.330 (8.4)	0.190 (4.8)	0.250 (6.4)	20	0.032 (0.81)	564R20TST10				
220			0.180 (4.6)				564R20TST22				
330			0.170 (4.3)				564R20TST33				
470			0.185 (4.7)				564R20TST47				
560			0.170 (4.3)				564R20TST56				
680			0.400 (10.2)				564R20TST68				
1000		0.430 (10.9)	564R20TSD10								
1500		0.460 (11.7)	564R20TSD15								
1800		0.530 (13.5)	0.170 (4.3)				564R20TSD18				
2200			0.160 (4.1)				564R20TSD22				
2700			0.170 (4.3)				564R20TSD27				
3300			0.160 (4.1)				564R20TSD33				
3900			0.680 (17.3)				564R20TSD39				
4700			0.170 (4.3)				564R20TSD47				
							0.375 (9.5)				564R20TSD47
<b>Y5S</b>											
1000	± 20	0.330 (8.4)	0.175 (4.4)	0.250 (6.4)	20	0.032 (0.81)	564R20TSSD10				
1500		0.400 (10.2)	0.170 (4.3)				564R20TSSD15				
1800		0.430 (10.9)					564R20TSSD18				
2200		0.460 (11.7)					564R20TSSD22				
2700		0.530 (13.5)					0.175 (4.4)	564R20TSSD27			
3300			564R20TSSD33								
3900			0.620 (15.7)					564R20TSSD39			
4700			0.680 (17.3)					0.170 (4.3)	564R20TSSD47		
5600		564R20TSSD56									
6800		0.720 (18.3)	0.375 (9.5)				564R20TSSD68				
<b>Y5U</b>											
1000		± 20	0.330 (8.4)				0.170 (4.3)	0.250 (6.4)	20	0.032 (0.81)	564R20GAD10
1500	0.330 (8.4)		0.170 (4.3)	564R20GAD15							
<b>Z5U</b>											
1800	± 20	0.360 (9.1)	0.170 (4.3)	0.250 (6.4)	20	0.032 (0.81)	564R20GAD18				
2200		0.400 (10.2)	0.175 (4.4)				564R20GAD22				
2700		0.430 (10.9)					564R20GAD27				
3300		0.490 (12.4)					564R20GAD33				
3900							564R20GAD39				
4700			564R20GAD47								
6800		0.560 (14.2)	0.170 (4.3)				564R20GAD68				
0.010 μF		0.680 (17.3)					0.375 (9.5)	564R20GAS10			
<b>Y5V</b>											
0.01 μF		± 20	0.620 (15.7)				0.170 (4.3)	0.375 (9.5)	20	0.032 (0.81)	564R20GASS10
0.05 μF	0.950 (24.1)		0.174 (4.4)	20	564R20GAS50						
0.10 μF	0.950 (24.1)		0.240 (6.1)	22	0.025 (0.64)	565R20GAP10					



ORDERING INFORMATION, CERAMIC 3 kV <sub>DC</sub>										
C (pF)	TOL. (%)	D <sub>max.</sub> DIAMETER INCH (mm)	T <sub>max.</sub> THICKNESS INCH (mm)	LS LEAD SPACE INCH (mm)	WIRE SIZE		ORDERING CODE			
					AWG	INCH (mm)				
<b>U2J (N750)</b>										
10	± 20	0.330 (8.4)	0.210 (5.3)	0.250 (6.4)	20	0.032 (0.81)	564R30GAQ10			
12			0.210 (5.3)				564R30GAQ12			
15			0.180 (4.6)				564R30GAQ15			
<b>R3L (N2200)</b>										
22	± 20	0.330 (8.4)	0.200 (5.1)	0.250 (6.4)	20	0.032 (0.81)	564R30GAQ22			
27			0.190 (4.8)				564R30GAQ27			
33			0.170 (4.3)				564R30GAQ33			
<b>X7R</b>										
47	± 20	0.330 (8.4)	0.230 (5.8)	0.250 (6.4)	20	0.032 (0.81)	564R30GAQ47			
56			0.190 (4.8)				564R30GAQ56			
68			0.200 (5.1)				564R30GAQ68			
100			0.180 (4.6)				564R30GAT10			
150			0.190 (4.8)				564R30GAT15			
220			0.175 (4.4)				564R30GAT22			
270			0.180 (4.6)				564R30GAT27			
330			0.175 (4.4)				0.180 (4.6)	564R30GAT33		
390								564R30GAT39		
470			± 10				0.400 (10.2)	0.180 (4.6)	0.375 (9.5)	20
680	0.175 (4.4)	564R30TST68								
1000	0.490 (12.5)	564R30TSD10								
1500	0.530 (13.5)	0.185 (4.7)		564R30TSD15						
1800		0.180 (4.6)		564R30TSD18						
2200	0.620 (15.7)	0.185 (4.7)		564R30TSD22						
2700		0.170 (4.3)		564R30TSD27						
3300	0.720 (18.3)	0.185 (4.7)		564R30TSD33						
3900		0.175 (4.4)		564R30TSD39						
4700	0.900 (22.9)	0.175 (4.4)		564R30TSD47						
6800		0.185 (4.7)	564R30TSD68							
<b>Y5S</b>										
1000	± 20	0.400 (10.2)	0.190 (4.8)	0.250 (6.4)	20	0.032 (0.81)	564R30TSSD10			
1500		0.460 (11.7)					564R30TSSD15			
1800		0.490 (12.4)					564R30TSSD18			
2200		0.530 (13.5)					564R30TSSD22			
2700		0.560 (14.2)					564R30TSSD27			
3300		0.620 (15.7)	0.185 (4.7)	564R30TSSD33						
3900				564R30TSSD39						
4700		0.680 (17.3)	0.375 (9.5)	564R30TSSD47						
5600		0.790 (20.0)	0.190 (4.8)	564R30TSSD56						
6800		0.900 (22.9)	0.205 (5.2)	564R30TSSD68						
<b>Y5U</b>										
680	± 20	0.330 (8.4)	0.175 (4.4)	0.250 (6.4)	20	0.032 (0.81)	564R30GAT68			
<b>Z5U</b>										
1000	± 20	0.330 (8.4)	0.195 (5.0)	0.250 (6.4)	20	0.032 (0.81)	564R30GAD10			
1500		0.360 (9.1)	0.190 (4.8)				564R30GAD15			
1800		0.400 (10.2)					564R30GAD18			
2200		0.430 (10.9)					564R30GAD22			
2700		0.460 (11.7)	0.200 (5.1)				564R30GAD27			
3300		0.490 (12.4)	0.185 (4.7)	564R30GAD33						
3900		0.530 (13.5)		564R30GAD39						
4700		0.620 (15.7)	0.195 (5.0)	564R30GAD47						
6800		0.680 (17.3)	0.185 (4.7)	0.375 (9.5)			564R30GAD68			
8200							564R30GAD82			
0.010 μF							0.720 (18.3)	564R30GAS10		
0.020 μF		0.720 (18.3)	0.265 (6.7)	22			0.025 (0.64)	565R30GASS20		
0.033 μF		0.900 (22.9)	0.240 (6.1)	22			0.025 (0.64)	565R30GASS33		
<b>Y5V</b>										
0.010 μF		± 20	0.720 (18.3)	0.185 (4.7)			0.375 (9.5)	20	0.032 (0.81)	564R30GASS10



ORDERING INFORMATION, CERAMIC 6 kV <sub>DC</sub>							
C (pF)	TOL. (%)	D <sub>max.</sub> DIAMETER INCH (mm)	T <sub>max.</sub> THICKNESS INCH (mm)	LS LEAD SPACE INCH (mm)	WIRE SIZE		ORDERING CODE
					AWG	INCH (mm)	
<b>C0G (NP0)</b>							
10	± 20	0.400 (10.2)	0.220 (5.6)	0.375 (9.5)	20	0.032 (0.81)	564R60GAQ10
<b>U2J (N750)</b>							
22	± 20	0.460 (11.7)	0.240 (6.1)	0.375 (9.5)	20	0.032 (0.81)	564R60GAQ22
<b>R3L (N2200)</b>							
33	± 20	0.400 (10.2)	0.230 (5.8)	0.375 (9.5)	20	0.032 (0.81)	564R60GAQ33
47		0.460 (11.7)	0.205 (5.2)				564R60GAQ47
<b>X5F</b>							
100	± 20	0.400 (10.2)	0.240 (6.1)	0.375 (9.5)	20	0.032 (0.81)	564R60GAT10
220			0.265 (6.7)				564R60GAT22
<b>X5S</b>							
330	± 20	0.400 (10.2)	0.260 (6.6)	0.375 (9.5)	20	0.032 (0.81)	564R60GAT33
<b>Y5U</b>							
470	± 20	0.400 (10.2)	0.265 (6.7)	0.375 (9.5)	20	0.032 (0.81)	564R60GAT47
560			0.240 (6.1)				564R60GAT56
<b>Z5U</b>							
1000	± 20	0.400 (10.2)	0.270 (6.9)	0.375 (9.5)	20	0.032 (0.81)	564R60GAD10
1500		0.460 (11.7)	0.280 (7.1)				564R60GAD15
2200		0.530 (13.5)	0.240 (6.1)				564R60GAD22
3300		0.620 (15.7)	0.260 (6.6)				564R60GAD33
4700		0.790 (20.0)					564R60GAD47
0.010 µF		0.950 (24.1)	0.250 (6.4)				564R60GAS10

ORDERING INFORMATION, CERAMIC 7.5 kV <sub>DC</sub>							
C (pF)	TOL. (%)	D <sub>max.</sub> DIAMETER INCH (mm)	T <sub>max.</sub> THICKNESS INCH (mm)	LS LEAD SPACE INCH (mm)	WIRE SIZE		ORDERING CODE
					AWG	INCH (mm)	
<b>X5F</b>							
100	± 20	0.530 (13.5)	0.310 (7.9)	0.500 (12.7)	20	0.032 (0.81)	564R75GAT10
470		0.620 (15.7)	0.270 (6.9)				564R75GAT47
<b>Y5U</b>							
1000	+ 80/- 20	0.620 (15.7)	0.320 (8.1)	0.500 (12.7)	20	0.032 (0.81)	564R75GAD10
<b>Z5U</b>							
2500	+ 80/- 20	0.620 (15.7)	0.280 (7.1)	0.500 (12.7)	20	0.032 (0.81)	564R75GAD25

**TAPE AND REEL OPTIONS**

Part number codes and specifications for tape and reel packaging are found in the general information document - find web-link below.

RELATED DOCUMENTS	
General Information	<a href="http://www.vishay.com/doc?23140">www.vishay.com/doc?23140</a>



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Vishay:

[30GASS40](#) [30GASS20](#) [20TSD15QA](#) [30GAT33KA](#) [75GAT10](#) [75GAD25](#) [75GAT47](#) [20TSD10PH1A](#) [30GAD10PM](#)  
[565RTGP10](#) [564R20GAD33](#) [564R30GAD33](#) [564R30GAD22](#) [564R20GAD10](#) [564R20GAP10](#) [564R20GAS10](#)  
[564R20GASS10](#) [564R20TSD22](#) [564R20TST22](#) [564R2DF0T18](#) [564R2DF0T33](#) [564R30GAD10](#) [564R30GAD15](#)  
[564R30GAD47](#) [564R30GAD50](#) [564R30GAD68](#) [564R30GAD82](#) [564R30GAQ10](#) [564R30GAQ15](#) [564R30GAQ27](#)  
[564R30GAQ33](#) [564R30GAQ56](#) [564R30GAQ68](#) [564R30GAS40](#) [564R30GASS10](#) [564R30GASS20](#) [564R30GASS33](#)  
[564R30GAT10](#) [564R30GAT22](#) [564R30GAT27](#) [564R30GAT33](#) [564R30GAT39](#) [564R30GAT47](#) [564R30GAT68](#)  
[564R30TSD10](#) [564R30TSD22](#) [564R30TSD33](#) [564R30TSD47](#) [564R3DF0D10](#) [564R3DF0D12](#) [564R3DF0D18](#)  
[564R3DF0Q22](#) [564R3DF0Q27](#) [564R3DF0Q33](#) [564R60GAD10](#) [564R60GAD33](#) [564R60GAD47](#) [564R60GAQ10](#)  
[564R60GAQ22](#) [564R60GAQ33](#) [564R60GAQ47](#) [564R60GAT22](#) [564R60GAT33](#) [564R60GAT47](#)  
[564RC0GAA202EC100J](#) [564RC0GAA202EF120J](#) [564RC0GAA202EF150J](#) [564RC0GAA202EF180J](#)  
[564RC0GAA202EF200J](#) [564RC0GAA202EG270J](#) [564RC0GAA202EG330J](#) [564RC0GAA302EH180J](#)  
[564RC0GAA302EJ220J](#) [564RC0GAA302EJ680J](#) [564RC0GAA302EK270J](#) [564RC0GAA302EK330J](#)  
[564RC0GAA302EL390J](#) [564RC0GAA302EL470J](#) [564RC0GAA302EL680J](#) [564RC0GAA302EP101J](#)  
[564RC0GAA302EP121J](#) [564RC0GAA302EP151J](#) [564RC0GAA302ES181J](#) [564RC0GAA302ES271J](#)  
[564RC0GHJ602EM470J](#) [564RC0HAE402EE4R7D](#) [564RC0HAE402EE5R6D](#) [564RC0JAE402EE3R0D](#)  
[564RC0JAE402EE3R9D](#) [564RC0KAA502EE1R0C](#) [564RC0KAE402EE1R0D](#) [564RC0KAE402EE2R0D](#)  
[564RC0KNA202EC1R5D](#) [564RX5EAA302EF271K](#) [564RX5RAJ402EG911M](#) [564RX5SAA402EP472M](#)  
[564RX7RAA602EF271K](#) [564RX7RAA602EK152M](#) [564RX7RBA202EE751K](#) [564RX7RBJ202EL103K](#)