

**SPECIFICATIONS**

**Mechanical**

**Mating Force:** 3.50Kg (7.71Lb) max.  
**Unmating Force:** 1.00Kg (2.20Lb) min.  
**Durability:** 1500 Cycles


**Electrical**

**Current Rating:** 1.5A  
**Contact Resistance:** 30mΩ max.  
**Dielectric Withstanding Voltage:** 500V AC/1min min.  
**Insulation Resistance:** 1000MΩ min.


**Physical**

**Housing:** Thermoplastic, UL 94V-0 rated  
**Contact:** Copper alloy  
**Shell:** Stainless steel  
**Plating:** See "ORDERING INFORMATION"  
**Operating Temperature:** -55°C to +85°C

**UB Series**  
**Right Angle, T/H**  
**8 Pos.**



**DRAWING**



**ORDERING INFORMATION**

**PRODUCT NO: UB 1 1 1 2 C - 8FDE - 4 F**

- USB Series
- Terminator Type  
1=Right Angle Type
- Contact Design Type  
1=Female
- NO. of Pos  
1=4 Pos
- Lead Free
- Package Code  
4=Tray Packing
- Extension Code
- Contact Area Plating  
C=30u" Pd/Ni+Gold Flash
- Profile Height  
2=4.13 mm