

# 205 RS series



## features



- Direct replacement for T1 ¾ Midget Groove S5.7s
- Reverse polarity options available
- Water clear lens
- Centre contact Anode as standard
- Low current versions available
- Warm white LEDs may be used behind coloured lens as a true replacement for a filament lamp
- Pack Quantity = 20 Pieces

## specifications

Ordering information and typical characteristics (Ta = 25°C)

RS Part Number	Marl Part Number	Colour	Voltage Vac/dc	Current DC (mA)	Luminous Intensity (mcd)	Wave Length (nm)	Operating Temp. (°C)	Storage Temp. (°C)	De-rating Graphs
2387589	205-501-21-38	Red	12 Vdc	10	600	630	-40 - +80	-40 - +100	D
2387630	205-501-22-38	Red	24 Vdc	10	600	630	-40 - +80	-40 - +100	D
2387680	205-501-23-38	Red	24-28 Vdc	8	600	630	-40 - +80	-40 - +100	D
2387602	205-521-21-38	Yellow	12 Vdc	10	600	585	-40 - +80	-40 - +100	D
2387652	205-521-22-38	Yellow	24 Vdc	10	600	585	-40 - +80	-40 - +100	D
2387703	205-521-23-38	Yellow	24-28 Vdc	8	600	585	-40 - +80	-40 - +100	D
2387595	205-532-21-38	Green	12 Vdc	10	800	515	-40 - +80	-40 - +100	F
2387646	205-532-22-38	Green	24 Vdc	10	800	515	-40 - +80	-40 - +100	F
2387696	205-532-23-38	Green	24-28 Vdc	8	800	515	-40 - +80	-40 - +100	F
2387618	205-930-21-38	Blue	12 Vdc	10	230	465	-30 - +85	-40 - +100	U
2387674	205-930-22-38	Blue	24 Vdc	10	230	465	-30 - +85	-40 - +100	U
469923	205-993-21-38	Warm White	12 Vdc	10	Call	* See pg.2	-30 - +85	-40 - +100	I
469812	205-993-22-38	Warm White	24 Vdc	10	Call	* See pg.2	-30 - +85	-40 - +100	I
469816	205-993-23-38	Warm White	24-28 Vdc	8	Call	* See pg.2	-30 - +85	-40 - +100	I
2829960	205-997-21-38	White	12 Vdc	10	1100	* See pg.2	-30 - +85	-40 - +100	I
2829976	205-997-22-38	White	24 Vdc	10	1100	* See pg.2	-30 - +85	-40 - +100	I
2829982	205-997-23-38	White	24-28 Vdc	8	1100	* See pg.2	-30 - +85	-40 - +100	I

^ = Voltage for 20mA product is Vf at 20mA, not Vopr

- Products must be de-rated according to the de-rating information. Each de-rating graph refers to specific LEDs. Please refer to graphs on page 2.

- Luminous intensity is measured at 20mA on a discrete LED unless otherwise stated.


© marl international limited technical documentation has been designed by marl international limited for the intention of providing information, which must not be copied or released to a third party without prior written consent from marl international limited. the information provided does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. no responsibility can be assumed for inaccuracies or printing errors. marl international limited reserve the right to alter without notice the specification or any conditions of supply for product or service.



# 205 RS series



## technical data



Green dot on base of product signifies reverse polarity. Colour dot on LED denotes LED colour.

Dimensions in mm (typical)  
Not to scale




Lamp Base Style	Series	Metric Equivalent (mm)	Max. Power Dissipation (mW)
T1 3/4 Midget Groove S5.7s	205	5	500

899F	*Typical emission colour Warm White			
x	0.4255	0.4390	0.4680	0.4519
y	0.4000	0.4310	0.4385	0.4086

997F-C	*Typical emission colour White			
x	0.31	-	-	-
y	0.32	-	-	-

Intensities (lv) and colour shades of white (x,y co-ordinates) may vary between leds within a batch

## de-rating information




© marl international limited technical documentation has been designed by marl international limited for the intention of providing information, which must not be copied or released to a third party without prior written consent from marl international limited. the information provided does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. no responsibility can be assumed for inaccuracies or printing errors. marl international limited reserve the right to alter without notice the specification or any conditions of supply for product or service.



# 205 RS series



## de-rating information continued



© marl international limited technical documentation has been designed by marl international limited for the intention of providing information, which must not be copied or released to a third party without prior written consent from marl international limited. the information provided does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. no responsibility can be assumed for inaccuracies or printing errors. marl international limited reserve the right to alter without notice the specification or any conditions of supply for product or service.



# 205 RS series



also available

Part numbers also available in the 205 series:

Part Number	Colour	Voltage Vopr
205-501-04-38	Red	20 mA dc
205-501-20-38	Red	5/6 Vdc
205-501-24-38	Red	48 Vdc
205-501-30-38	Red	5/6 Vdc RP
205-501-31-38	Red	12 Vdc RP
205-501-32-38	Red	24 Vdc RP
205-502-04	Red	20 mA dc
205-512-04	Green	20 mA dc
205-514-21	Green	12 Vdc
205-521-04-38	Yellow	20 mA dc
205-521-20-38	Yellow	5/6 Vdc
205-521-24-38	Yellow	48 Vdc
205-521-32-38	Yellow	24 Vdc RP
205-521-33-38	Yellow	28 Vdc RP
205-521-34-38	Yellow	48 Vdc RP
205-532-04-38	Green	20 mA dc
205-532-20-38	Green	5/6 Vdc
205-532-22-51	Green	24 Vdc
205-532-24-38	Green	48 Vdc
205-532-31-38	Green	12 Vdc RP
205-532-32-38	Green	24 Vdc RP
205-532-33-29	Green	28 Vdc RP
205-532-33-38	Green	28 Vdc RP
205-532-34-38	Green	48 Vdc RP
205-899-33-38	Warm White	28 Vdc RP
205-899-33-50	Warm White	28 Vdc RP
205-930-20-38	Blue	5/6 Vdc
205-930-23-38	Blue	28 Vdc
205-930-24-38	Blue	48 Vdc
205-993-00-50	Warm White	15 Vdc RP
205-993-04-38	Warm White	20 mA dc
205-993-20-38	Warm White	5/6 Vdc
205-993-24-38	Warm White	48 Vdc
205-993-32-38	Warm White	24 Vdc RP
205-993-33-38	Warm White	28 Vdc RP
205-993-42-38	Warm White	15 Vdc
205-993-46-38	Warm White	35 Vdc
205-993-53-52	Warm White	50 Vdc
205-993-53-53	Warm White	50 Vdc
205-993-53-54	Warm White	50 Vdc
205-993-53-55	Warm White	50 Vdc
205-993-73-38	Warm White	28 Vac 50 Hz
205-997-04-38	White	20 mA dc
205-997-13-38	White	20 mA dc RP
205-997-20-38	White	5/6 Vdc
205-997-24-38	White	48 Vdc
205-997-32-38	White	24 Vdc RP
205-997-34-38	White	48 Vdc RP
205-997-42-38	White	15 Vdc

RP = Reverse Polarity

© marl international limited technical documentation has been designed by marl international limited for the intention of providing information, which must not be copied or released to a third party without prior written consent from marl international limited. the information provided does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. no responsibility can be assumed for inaccuracies or printing errors. marl international limited reserve the right to alter without notice the specification or any conditions of supply for product or service.



BS EN ISO 9001:2008 approved manufacturer

# 205 RS series



## design considerations

### Single-Chip LEDs

All devices feature water clear high intensity LEDs as standard. In devices where discrete LEDs are used, the single chip LED devices have been modified by the removal of the domed portion of the encapsulation (flat-topped) to provide even illumination of switches and annunciators. Non flat topped versions are also available. Flat-topping does not apply to devices using surface-mounted device (SMD) LEDs.

### Product Evaluation

Filament replacement LEDs have been specifically designed to meet the primary objective of providing improved reliability. As this product range is suitable for both new-build and retro-fit, (sometimes in very old systems), a wide range of illuminated push button switches and lamp holders can be encountered. Due to subjectivity, evaluation of the LED type is recommended, (samples of all standard models are available). Care should be taken to correctly simulate operating ambient light conditions to ensure that the correct device has been selected to maximise viewing characteristics such as viewing angle, colour compatibility and on/ off contrast ratio.

### Electro-Static Discharge (ESD)

Build up of electro-static discharge occurs in many situations involving people moving and handling products. The range of possible situations is very diverse but voltage levels as high as several thousand volts can and do arise in many individual situations. When an operator charged up to these levels handles a static sensitive device, there is a very probable likelihood that the device will be irreversibly damaged. It is essential that precautions are taken at all stages during manufacture and assembly of these products. Although LEDs were never considered to be static sensitive devices, changes in manufacturing technology and materials used to produce higher intensity products over a large range of the wavelength spectrum have changed this. Marl has an approved system of ESD control from goods in, through production and into final packing and despatch. Marl recommend all users of LED based products follow the guidelines of BS 100015.

### Power De-Rating

The forward voltage/ current value of an LED is dependant upon the ambient temperature of the environment in which it is operated. Therefore, care must be taken to operate the LED at the correct voltage/ current values, depending upon the ambient temperature. Consequently, a recommendation regarding operating voltages and currents is given in order to address these temperature effects. This recommendation is termed 'de-rating'. It is usual for forward voltages and currents to be specified for ambient temperature of 25°C. However, because the values of these qualities vary with temperature, marl should be contacted if the device is to be operated at a temperature significantly higher than 25°C. Marl accept no liability for any product that is operated higher than the stated voltage.

© marl international limited technical documentation has been designed by marl international limited for the intention of providing information, which must not be copied or released to a third party without prior written consent from marl international limited. the information provided does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. no responsibility can be assumed for inaccuracies or printing errors. marl international limited reserve the right to alter without notice the specification or any conditions of supply for product or service.

