

Note: This datasheet may be out of date. Please download the latest datasheet of NFE61HT332Z2A9# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NFE61HT332Z2A9%23

"#" indicates a package specification code.

NFE61HT332Z2A9#

In Production RoHS REACH 0200

< List of part numbers with package codes > NFE61HT332Z2A9L NFE61HT332Z2A9K

NFE61HT332Z2A9B



Appearance & Shape



Packaging Information

|--|

0.7±0.2	2.6±0.3	0.7±0.2	
(1)	(2)	(3)	
	Ĺ		
-	6.8 ^{+0.3}	•	1.6±0.3

(in mm)

Applications Automotive Usage Powertrain/Safety

Minimum Packaging Specifications Order Quantity L 2500 180mm Embossed Tape Κ 330mm Embossed Tape 8000 В Bulk(Bag) 500



Features

The T-type chip EMI Filter NFE61HT series consists of a feedthrough capacitor and ferrite beads.

Features

- 1. Its large rated current of 2A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4.33 to 3,300pF lineups can be used in signal lines.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

NFE61HT332Z2A9#

Note: This datasheet may be out of date. Please download the latest datasheet of NFE61HT332Z2A9# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NFE61HT332Z2A9%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	2706
Length	6.8mm
Length Tolerance	+0.3/-0.5mm
Width	1.6mm
Width Tolerance	±0.3mm
Thickness	1.6mm
Thickness Tolerance	±0.3mm
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.062g
Number of Circuit	1
Rated Current	2A
Rated Voltage	100Vdc
Withstanding Voltage	250Vdc
Insulation Resistance(min.)	1000ΜΩ
Capacitance	3300pF
Capacitance Tolerance	80/-20%
Size Code (in mm)	6816

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





NFE61HT332Z2A9#

Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NFE61HT332Z2A9# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NFE61HT332Z2A9%23

"#" indicates a package specification code.




Product Data





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

