

Polyimide adhesive tape

# No.360UL


## Features

---

- Offers superior electrical insulation.
- Offers superior heat resistance. (Rated Thermal Level 180°C)
- Offers superior flame-retardant. UL 510 FR recognized

## Structure

---



## Applications

---

- Electrical insulation and heat resistance.

## 特 性

---

Table 1 General Properties

Item	Unit	No. 360UL	
Total thickness (Backing)	mm	0.060 (0.025)	0.090 (0.050)
Color	—	Amber	
Peel adhesion	N/19mm	5.4	5.4
Tensile strength	N/19mm	145	250
Elongation	%	65	65
Breakdown Voltage	kv	8.0	11.0

- For inquiries ...Application Engineering Dept, Technical Support Center EYES Gr  
E-mail : eyes@nitto.co.jp TEL : 81-48-571-3340 FAX : 81-48-571-3325

**Notes:** This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.