


ME 040-500 Closed ends header



Pitch: 5.00mm(0.197inch)






SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 400V
負載電流	Rated Current	Bemessungsstrom	16A	16A
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
焊針	Solder Pin	Lötstift	□1.0mm, Brass, Tin plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.5mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
ME040-50002	11.6	0.457
ME040-50003	16.6	0.654
ME040-50004	21.6	0.850
ME040-50005	26.6	1.047
ME040-50006	31.6	1.244
ME040-50007	36.6	1.441
ME040-50008	41.6	1.638
ME040-50009	46.6	1.835
ME040-50010	51.6	2.031
ME040-50011	56.6	2.228
ME040-50012	61.6	2.425
ME040-50013	66.6	2.622
ME040-50014	71.6	2.819
ME040-50015	76.6	3.016
ME040-50016	81.6	3.213
ME040-50017	86.6	3.409
ME040-50018	91.6	3.606
ME040-50019	96.6	3.803
ME040-50020	101.6	4.000
ME040-50021	106.6	4.197
ME040-50022	111.6	4.394
ME040-50023	116.6	4.591
ME040-50024	121.6	4.787



PCB Layout

