

NAGAKI



N.G.K

GRIPPING
THE GLOBE



Our **Energy**, Your Power.

www.tengroup.com.au | Phone : 07 3212 8999

NGK NAGAKI

NAGAKI



NAGAKI
Since 1946 We can do it!



'Our tools are enabling linemen to work with the 3S of Safety, Strength and Speed to connect vital utilities such as power, rail and communication lines'



Hiroshima Office Since 1979
Kusyu Office & Factory Since 1993

NAGAKI SEIKI CO. LTD was established in April 1946. Designated by Osaka Gas Co., they began to manufacture pipe cutters while simultaneously establishing the engineering section to improve the quality of tools as well as the design, research and trial manufacturing of various tools.



The N.G.K. brand has been in use for 68 years and has since gained trust as a leader in tool manufacturing globally. Nagaki Japan manufactures superior quality wire rope grips, ratchet pullers, ratchet wrenches and tension meters/ dynamometers under the N.G.K. brand.

These products are manufactured to the highest standards to suit a range of industry applications.



N.G.K.
GRIPPING THE GLOBE

NGK Web Strap Hoists


GRIPPING THE GLOBE

NGK web strap hoists feature insulated super-strength 32mm wide web straps, insulated fiberglass handles and a special handle neck that will bend if the unit is overloaded to prevent damage to the puller and injury to the operator.



Part No: N-1500P-EX

- Convertible series with 3 hooks
- Lightweight
- Insulated handles rotate 360°



Part No	Pull (m)	Strap Length		WLL (kN/T)	Handle Length	Wt
		Min.	Max.			
N-1500P-EX	1.5 Single/ 3.0 Double	500mm	2000/3500mm	15 (dbl) 7.5 (sgl)	460mm	5kg
N-1500P-EX-H	1.5 Single/ 3.0 Double	500mm	2000/3500mm	15 (dbl) 7.5 (sgl)	460mm	5.1kg

TEN offer web hoist refurbishment services and repairs on all NGK Hoists

Part No: N-1500P-EX-H

- For hot line work
- Detachable handle
- Convertible series with 3 hooks



Part No: N-1000P & N-1500P

- Lightweight
- Insulated handles rotate 360°

Insulated handles rotate 360° on all models



Part No	Pull	Strap Length		WLL	Handle Length	Wt
		Min.	Max.			
N-1000P	1.5m	440mm	1940mm	10kN/1T	400mm	3.3kg
N-1500P	1.5m	470mm	1970mm	15kN/1.5T	460mm	4.6kg



TEN Web Strap Hoist Bag
Part No: TENM426

- Quality canvas carry bag
- Protect hoists with handles on
- Webbing handle & heavy duty zips
- Made from durable tear stop canvas

Need a storage solution?

Part No	Length	Wt
TENM426	740mm	0.5kg

NGK Chain Ratchet Hoists **NAGAKI**

Part No: MODEL3000, MODEL4000, MODEL6000

- Lightweight aluminium housing with 5mm diameter alloy chain link and forged hooks
- 360° rotating handle of 430mm length
- Safety hook attachment
- Special length chains available on request



MODEL3000

Part No	Attachment Style	Chain Dia.	Lift		WLL	Handle Length	Wt
			Min.	Max.			
MODEL3000	Safety Hook	5mm	480mm	2000mm	30kN/3T	430mm	8kg
MODEL4000	Bolted Clevis	5mm	580mm	2180mm	40kN/4T	430mm	12kg
MODEL6000	Bolted Clevis	5mm	650mm	2250mm	60kN/6T	430mm	19kg

Part No: RICKY-2, RICKY-3

- Lightweight
- 5mm diameter alloy chain link
- 360° rotating handle of 230mm length
- Safety hook attachment



RICKY-2

RICKY-3

Part No	Pull	Lift		WLL	Handle Length	Wt
		Min.	Max.			
RICKY-2	1.5m	300mm	1800mm	7.5kN/0.75T	230mm	4kg
RICKY-3	1.5m	350mm	1850mm	15kN/1.5T	230mm	5kg

NGK chain hoists suitable for pulling, tensioning and securing applications

NGK Ratchet Wrench **NAGAKI**


Part No: BY-3

- Four sizes in one
- Plastic ergonomic non-slip handle with grips

FOUR sizes in ONE



D	10mm	12mm	16mm	20mm
B	17mm	19mm	24mm	30mm



NGK Grips **GRIPPING THE GLOBE**

Part No: MINI-GRIP

- Steel rod, barbed & messenger wire



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
1mm	10mm	5kN	-	16mm	0.3kg

Part No: 1TON-L-GRIP

- Bare Cu wire, covered conductor & messenger wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
4mm	22mm	10kN	60mm	32mm	1.1kg

Part No: 2TON-L-GRIP

- Bare Cu wire, covered conductor & messenger wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
4mm	22mm	20kN	60mm	32mm	1.3kg

Part No: 2TON-W-GRIP

- Cu wire, wire rope, messenger wire & trolley wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	16mm	20kN	100mm	32mm	1.4kg

Part No: 3TON-GRIP

- Wire rope, messenger wire, Cu wire & trolley wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
8mm	22mm	30kN	120mm	34mm	3kg

Part No: 4TON-GRIP

- Wire rope, messenger wire, Cu wire & trolley wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
13mm	28mm	40kN	150mm	25mm	5kg

NGK Grips



Part No: AL-2TON-GRIP-L

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch
- Locking nut option

Locking nut option



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	20mm	20kN	100mm	32mm	1.5kg

Part No: AL-L-GRIP

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	22mm	10kN	60mm	32mm	1.1kg

Part No: AL-MIDDLE-GRIP

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	25mm	20kN	110mm	32mm	1.8kg

Part No: AL-LARGE-GRIP

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
16mm	32mm	20kN	110mm	32mm	2kg

Part No: AL-3TON-GRIP

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
8mm	22mm	30kN	120mm	34mm	3kg

Part No: AL-4TON-GRIP

- Bare Al & bare Cu
- Fine smooth jaws to minimise conductor damage
- Safety latch




Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
20mm	35mm	40kN	140mm	34mm	3.7kg

NGK Grips



Part No: HOT-M-GRIP

- Bare Al & bare Cu
- Hotline latch
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	25mm	20kN	-	50mm (L) 32mm (W)	2kg

Part No: SD-L-GRIP

- Steel rod, Cu wire & messenger wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
2.6mm	15mm	10kN	34mm	26mm	0.6kg

Part No: MIDDLE-L-GRIP

- Cu wire, covered wire & messenger wire
- Safety latch



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
5mm	25mm	20kN	110mm	32mm	1.8kg

NGK Grips

- Manufactured from high tensile alloy steel, hot forged, heat-treated, precision machined and zinc-plated
- Safety latch on all models
- Locking nut option on some models
- Special shaped pulling eyes suit all brands of strap pullers



Part No: ABC GRIP

- Aerial bundled wire
- Safety latch



Wire OD		WLL	Jaw Length	Wt
Min.	Max.			
16mm 4x35mm	28mm 4 x 95mm	8.5kN	190mm	3kg

Part No: TROLLEY-GRIP-2-L

- Trolley wire, messenger wire, wire rope & Cu railway wire (no bending on trolley)
- Safety latch
- Locking nut option

Locking nut option



Wire OD		WLL	Jaw Length	Eye Width	Wt
Min.	Max.				
8mm	20mm	20kN	150mm	25mm	2.8kg

NGK Dynamometers/ Tension Meters

NAGAKI


Part No: A-3 to A-50

NGK Dynamometers feature lightweight, compact and rugged construction. Available in capacities from 3kN to 50kN, all models have a large face dial for easily reading measurements on the job. All dynamometers are serial numbered and come supplied in a heavy duty fabric carry case with calibration certificate.

- Precise measurement of tension and loads
- Kilogram/force (kN) large face dial display
- Accuracy $\pm 3\%$
- Plated to resist corrosion

Part No	Capacity	Graduation (Gauge Increments)	Dimensions			Wt
			A	B	C	
A-3	3kN/0.3T	30N/3kg	110mm	65mm	16mm	0.7kg
A-10	10kN/1T	200N/20kg	135mm	65mm	16mm	0.8kg
A-20	20kN/2T	500N/50kg	135mm	65mm	16mm	1.2kg
A-30	30kN/3T	500N/50kg	150mm	80mm	28mm	2kg
A-50	50kN/5T	1kN/100kg	260mm	95mm	28mm	3kg

Used to measure tension in wires, belts and cables, the NGK tension meter features two pulling eyes, connected to an analog indicator. This allows the user to accurately monitor tension and adjust equipment and loads accordingly.



A-3 Model



A-10 Model

TEN Group : Australia

The Energy Network (Australia) Pty Ltd

ABN 72 093 052 441



QLD :65 Wentworth Pl
VIC :24 Deans Court
WA :4/15 Baile Rd
NSW :2/22 Hudson Ave

WORKSHOP BANYO 4014
WORKSHOP DANDENONG STH 3175
WORKSHOP CANNING VALE 6155
CASTLE HILL 2154

P | F +61 7 3212 8999 | 8998 M 0400 077 819
P | F +61 3 9793 1622 | 1644 M 0408 228 473 | 0400 968 238
+61 8 9455 5574 M 0400 029 026
P | F +61 2 9899 5488 | 5477 M 0407 009 316