



ELECTRICAL CHARACTERISTICS:
 R25C=10K OHMS ±5%
 BETA=3435

OPERATING TEMPERATURE: -55C TO 105C
 THERMAL TIME CONSTANT: 5sec MAX

MECHANICAL CHARACTERISTICS:
 LEADS:
 #28 AWG SILVER PLATED SOLID COPPER
 CONDUCTOR, BLACK KYNAR INSULATION
 QTI P/N: QT01003-007

POLYOLEFIN HEATSHRINK, LENGTH=0.25"
 QTI P/N: QT01010-056-5

HOUSING:
 FLAT KAPTON SURFACE PROBE
 QTI P/N: QT01018-048

NOTES:

	INITIAL	DATE
DRAWN	BR	5/13/09
ENG APPR.	<i>Ray Roehner</i>	05 13, 2009
MAT APPR.	<i>Jim Davis</i>	May 14, 2009
Q.A. APPR.	<i>Daniel & Ann</i>	May 14, 2009



2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: **QT06005-334** REV -

SIZE **A** DWG. NO. QT06005-334.SLDDRW

DATE	REVISION	INITIAL
5/13/09	-	BR

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.