

AC centrifugal blowers

dual inlet, Ø 225



- **Material:** scroll housing and impeller made of galvanised sheet steel
- **Mounting:** EW-motor anti-vibration mounted on both sides

ebm-papst • Mulfingen

Nominal data		Characteristic	Voltage	Frequency	Air flow	Speed/rpm	Power input	Current draw	Capacitor	Noise level	Min. back pressure	Perm. amb. temp.	Mass
Type	Motor	VAC	Hz	m³/h	min⁻¹	W	A	µF/VDB	dB(A)	Pa	°C	kg	
D4D 225-CC01 -02 ⁽¹⁾	M4D074-LA	①	230/400	50	2980	1000	680	1,15	---	64	0	45	12,5
			230/400	60	2430	1050	700	1,25	---	62	100	35	
D4E 225-BC01 -02	M4E074-LA	②	230	50	2600	1100	700	3,05	25 / 400	67	20	40	12,1
D4E 225-CC01 -02 ⁽¹⁾	M4E074-LA	③	230	50	2650	1150	650	2,84	25 / 400	65	100	40	12,4
D6E 225-FB07 -02 ⁽¹⁾	M6E068-LA	④	230	50	2680	800	365	1,60	10 / 450	59	20	40	12,5
			230	60	2480	900	410	1,80	10 / 450	59	80	40	


subject to alterations

⁽¹⁾ Data collected via exhaust duct of 1 m length serving as diffuser


	n [min⁻¹]	P ₁ [W]
① ①	1110	600
① ②	1300	385
④ ①	850	330
④ ②	940	245

	n [min⁻¹]	P ₁ [W]
② ①	1200	660
② ②	1370	480
③ ①	1170	680
③ ②	1300	550

Characteristics



Characteristics



AC centrifugal blowers

dual inlet, Ø 225



- **Material:** scroll housing and impeller made of galvanised sheet steel
- **Mounting:** EW-motor anti-vibration mounted on both sides, mounting brackets on request
- **Approval:** complying with EN 60034-1

ebm-papst • Mulfingen

Nominal data		Characteristic	Voltage	Frequency	Air flow	Speed/rpm	Power input	Current draw	Capacitor	Noise level	Min. back pressure	Perm. amb. temp.	Mass
Type	Motor	VAC	Hz	m ³ /h	min ⁻¹	W	A	µF/VDB	dB(A)	Pa	°C	kg	
D4D 225-FH02 -01 ⁽¹⁾⁽²⁾	M4D094-LA	①	400 Y	50	3870	1300	950	1,82	---	75	0	85	15,6
			400 Y	60	4030	1350	1320	2,40	---	76	0	40	
D4D 225-GH02 -01 ⁽¹⁾⁽²⁾⁽³⁾	M4D094-LA	②	400 Y	50	4400	1230	1140	2,10	---	76	0	70	15,6
			400 Y	60	3940	1360	1280	2,30	---	74	150	50	
D4E 225-EH01 -01 ⁽¹⁾	M4E094-LA	③	230	50	3730	1230	1060	5,38	10 / 450	74	0	55	16,7
			230	60	3140	1410	1085	5,24	10 / 500	70	200	45	
D4E 225-DH01 -01 ⁽¹⁾⁽³⁾	M4E094-LA	④	230	50	3700	1230	1060	5,38	10 / 450	72	100	55	16,7
			230	60	3200	1370	1120	5,40	10 / 500	69	250	45	

subject to alterations

⁽¹⁾ Insulation class "F"


⁽²⁾ 400 VAC Δ/Y for two speed steps available on request

⁽³⁾ Data collected via exhaust duct of 1 m length serving as diffuser


	n [min ⁻¹]	P ₁ [W]
① ①	1360	717
① ②	1420	454
② ①	1320	877
② ②	1390	589

	n [min ⁻¹]	P ₁ [W]
③ ①	1330	802
③ ②	1410	530
④ ①	1270	947
④ ②	1380	652

Characteristics



Characteristics



Dimensions

Type	C	D	E	S
D4D 225-FH02 -01	200	180	146	90
D4D 225-GH02 -01	304	284	250	180
D4E 225-EH01 -01	200	180	146	90
D4E 225-DH01 -01	304	284	250	180

