

Molding Power Inductors

BDCL Series



BDCL Series provides high current in compact package size with magnetically shielded construction. This power inductor is an excellent power solution for space-limited devices.


Features

- RoHS, Halogen Free and REACH Compliance
 - Monolithic, magnetically shielded
 - Capable for large current


Applications

- Smartphones, tablets and wearable devices
 - HDD, SSD and PC peripheral devices
 - DSC, camcoders
 - PND
 - DC/DC converters

Product Identification




Shape and Dimensions



Dimensions in mm

TYPE	A	B	C	D
BDCL00201610	2.0±0.2	1.6±0.2	1.0Max	0.5±0.3
BDCL00201612	2.0±0.2	1.6±0.2	1.2Max	0.5±0.3
BDCL00252010	2.5±0.2	2.0±0.2	1.0Max	0.6±0.3
BDCL00252012	2.5±0.2	2.0±0.2	1.2Max	0.6±0.3

Recommended Pattern



Dimensions in mm

TYPE	A	B	C
BDCL00201610	0.7	2.3	1.8
BDCL00201612	0.7	2.3	1.8
BDCL00252010	1.2	2.8	2.3
BDCL00252012	1.2	2.8	2.3

Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00201610R24MS1	0.24	20	2	40(28)	4.2(6.0)	4.0(4.5)
BDCL00201610R33MS1	0.33	20	2	48(40)	4.0(5.5)	3.5(3.8)
BDCL00201610R47MS1	0.47	20	2	54(44)	3.2(5.0)	3.0(3.6)
BDCL00201610R56MS1	0.56	20	2	59(46)	2.8(4.6)	2.8(3.3)
BDCL00201610R68MS1	0.68	20	2	72(55)	2.7(4.2)	2.4(3.0)
BDCL002016101R0MS1	1.0	20	2	96(81)	2.2(3.4)	2.0(2.3)
BDCL002016101R5MS1	1.5	20	2	150(122)	2.1(2.8)	1.6(2.0)
BDCL002016102R2MS1	2.2	20	2	204(170)	2.0(2.4)	1.3(1.6)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Rated current : Isat or Irms, whichever is smaller
- Absolute maximum voltage 20VDC
- Measure Equipment :



L : Agilent E4991/HP4286A+16197A (or equivalent), 2MHz 0.2V

RDC : CHEN HWA502BC/HP4338B (or equivalent)

Isat : Agilent E4980A+HP42841A (or equivalent)

Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer





Electrical Characteristics

Part Number	Inductance (μ H)	Tolerance (\pm %)	Test Frequency (MHz)	RDC($m\Omega$) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00201610R24ML1	0.24	20	2	30(23)	5.0(6.0)	3.8(4.4)
BDCL00201610R47ML1	0.47	20	2	41(34)	4.0(4.5)	2.9(3.3)
BDCL00201610R68ML1	0.68	20	2	53(44)	3.3(3.6)	2.5(2.9)
BDCL002016101R0ML1	1.0	20	2	72(60)	2.8(3.2)	2.2(2.5)
BDCL002016102R2ML1	2.2	20	2	170(142)	1.8(2.1)	1.5(1.7)

Note: When ordering, please specify tolerance code. Tolerance: M= \pm 20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Rated current : Isat or Irms, whichever is smaller
- Absolute maximum voltage 20VDC
- Measure Equipment :
 - L : Agilent E4991A/HP4286A+16197A (or equivalent), 2MHz 0.2V
 - RDC : CHEN HWA502BC/HP4338B (or equivalent)
 - Isat : Agilent E4980A+HP42841A (or equivalent)
 - Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer



Molding Power Inductors

BDCL Series



Electrical Characteristics


Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00201612R24MS1	0.24	20	2	35(25)	5.5(6.5)	4.2(4.8)
BDCL00201612R47MS1	0.47	20	2	52(40)	3.8(5.1)	3.2(3.8)
BDCL00201612R68MS1	0.68	20	2	70(53)	3.3(4.8)	2.6(3.2)
BDCL002016121R0MS1	1.0	20	2	82(67)	3.1(3.9)	2.3(2.7)
BDCL002016121R5MS1	1.5	20	2	120(95)	2.6(3.2)	2.2(2.6)
BDCL002016122R2MS1	2.2	20	2	195(165)	2.0(2.6)	1.3(1.7)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%


- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Rated current : Isat or Irms, whichever is smaller
- Absolute maximum voltage 20VDC
- Measure Equipment :
 - L : Agilent E4991/HP4286A+16197A (or equivalent), 2MHz 0.2V
 - RDC : CHEN HWA502BC/HP4338B (or equivalent)
 - Isat : Agilent E4980A+HP42841A (or equivalent)
 - Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer

Inductance v.s DC Current



Temperature Change v.s DC Current



Molding Power Inductors

BDCL Series



Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00252010R24MS1	0.24	20	2	40(24)	7.5(9.5)	4.5(5.0)
BDCL00252010R47MS1	0.47	20	2	46(36)	5.2(6.5)	3.1(3.6)
BDCL00252010R68MS1	0.68	20	2	65(49)	3.8(5.0)	2.9(3.3)
BDCL002520101R0MS1	1.0	20	2	78(60)	3.4(4.3)	2.5(3.0)
BDCL002520101R5MS1	1.5	20	2	105(82)	3.2(4.0)	2.2(2.9)
BDCL002520102R2MS1	2.2	20	2	156(130)	2.6(3.2)	1.4(1.8)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)

- Isat for Inductance drop 30% from its value without current

- Irms for a 40°C temperature rise from 25°C ambient with current

- Rated current : Isat or Irms, whichever is smaller

- Absolute maximum voltage 20VDC

- Measure Equipment :

L : Agilent E4991/HP4286A+16197A (or equivalent), 2MHz 0.2V


RDC : CHEN HWA502BC/HP4338B (or equivalent)

Isat : Agilent E4980A+HP42841A (or equivalent)


Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer

Inductance v.s DC Current



Temperature Change v.s DC Current



Molding Power Inductors

BDCL Series



Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00252010R33ML1	0.33	20	2	31(25)	5.0(6.0)	3.8(4.4)
BDCL00252010R47ML1	0.47	20	2	35(29)	4.2(4.7)	3.4(3.9)
BDCL00252010R68ML1	0.68	20	2	48(40)	3.7(4.0)	3.0(3.5)
BDCL002520101R0ML1	1.0	20	2	65(54)	3.2(3.6)	2.6(3.0)
BDCL002520101R5ML1	1.5	20	2	94(78)	2.9(3.3)	2.1(2.4)
BDCL002520102R2ML1	2.2	20	2	120(100)	2.3(2.7)	1.8(2.1)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Rated current : Isat or Irms, whichever is smaller
- Absolute maximum voltage 20VDC
- Measure Equipment :



L : Agilent E4991/HP4286A+16197A (or equivalent), 2MHz 0.2V

RDC : CHEN HWA502BC/HP4338B (or equivalent)

Isat : Agilent E4980A+HP42841A (or equivalent)

Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer



Molding Power Inductors

BDCL Series



Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00252012R33MS1	0.33	20	2	35(27)	6.8(8.5)	4.0(4.6)
BDCL00252012R47MS1	0.47	20	2	39(29)	6.2(7.8)	3.7(4.4)
BDCL00252012R68MS1	0.68	20	2	46(40)	5.5(6.5)	3.3(3.7)
BDCL002520121R0MS1	1.0	20	2	59(45)	4.0(5.0)	3.0(3.5)
BDCL002520121R5MS1	1.5	20	2	70(62)	3.4(4.0)	2.5(2.7)
BDCL002520122R2MS1	2.2	20	2	115(102)	3.3(3.8)	2.0(2.3)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)

- Isat for Inductance drop 30% from its value without current

- Irms for a 40°C temperature rise from 25°C ambient with current

- Rated current : Isat or Irms, whichever is smaller

- Absolute maximum voltage 20VDC

- Measure Equipment :



L : Agilent E4991/HP4286A+16197A (or equivalent), 2MHz 0.2V

RDC : CHEN HWA502BC/HP4338B (or equivalent)

Isat : Agilent E4980A+HP42841A (or equivalent)

Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer



Molding Power Inductors

BDCL Series





Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (%)	Test Frequency (MHz)	RDC(mΩ) Max(Typ.)	Isat(A) Max(Typ.)	Irms(A) Max(Typ.)
BDCL00252012R47ML1	0.47	20	2	34(30)	5.2(6.0)	4.1(4.7)
BDCL002520121R0ML1	1.0	20	2	56(45)	3.6(4.5)	3.2(3.7)
BDCL002520122R2ML1	2.2	20	2	102(80)	2.5(3.0)	2.2(2.6)

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

- Operating temperature range - 40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Rated current : Isat or Irms, whichever is smaller
- Absolute maximum voltage 20VDC
- Measure Equipment :
L : Agilent E4991A+HP4286A+16197A (or equivalent), 2MHz 0.2V
RDC : CHEN HWA502BC/HP4338B (or equivalent)
Isat : Agilent E4980A+HP42841A (or equivalent)
Irms : Agilent 6641 SYSTEM DC POWER SUPPLY (or equivalent)

Test Instruments : E4991A Impedance / Material Analyzer



Molding Power Inductors

BDCL Series




Molding Power Inductors

BDCL Series




Packaging Specifications


Tape Dimensions



Tape Material



Reel Dimensions



Dimensions in mm

TYPE	Tape Dimensions							Reel Dimensions				Quantity
	A	B	T	W	P	F	K	A	B	C	D	
BDCL00201610	1.90	2.30	0.22	8	4	3.5	1.15	178	60	12	1.5	3000
BDCL00201612	1.90	2.30	0.22	8	4	3.5	1.15	178	60	12	1.5	3000
BDCL00252010	2.25	2.80	0.22	8	4	3.5	1.15	178	60	12	1.5	3000
BDCL00252012	2.30	2.80	0.22	8	4	3.5	1.35	178	60	12	1.5	3000

For More Information:

Americas - prodinfo_power_americas@yageo.com | **Europe** - prodinfo_power_emea@yageo.com | **Asia** - prodinfo_power_asia@yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2022. Pulse Electronics, Inc. All rights reserved.