


NTC Thermistors

Thermistor for inrush current limiting

Temperature range -25 °C ... +170 °C
 Rated temperature +25 °C



FN0257-3

| Type | R_{25} | $I_{25 \text{ max}}$ | Ordering code | Min. qty. | Max. qty. | Price each in DM | | | | |
|------|----------|----------------------|---------------|-----------|-----------|------------------|-------|-------|-------|--------|
| | Ω | A | | | | Min. qty. + | 100 + | 250 + | 500 + | 1000 + |

R_R tolerance $\pm 20\%$

| | | | | | | | | | | |
|------------------|-------|------|---------------|----|------|------|------|------|-----|-----|
| ■ S234/ 1,0/20% | 1,0 | 11,5 | B57234-S109-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 2,2/20% | 2,2 | 9,0 | B57234-S229-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 2,5/20% | 2,5 | 8,4 | B57234-S259-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 4,7/20% | 4,7 | 6,6 | B57234-S479-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 5,0/20% | 5,0 | 6,4 | B57234-S509-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 7,0/20% | 7,0 | 6,0 | B57234-S709-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 10,0/20% | 10,0 | 5,0 | B57234-S100-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 15,0/20% | 15,0 | 4,0 | B57234-S150-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 22,0/20% | 22,0 | 4,0 | B57234-S220-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 33,0/20% | 33,0 | 3,3 | B57234-S330-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 40,0/20% | 40,0 | 3,4 | B57234-S400-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/ 60,0/20% | 60,0 | 4,0 | B57234-S600-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ■ S234/220,0/20% | 220,0 | 2,0 | B57234-S221-M | 50 | 2000 | 1,49 | 1,27 | 1,11 | -98 | -85 |
| ▼ S237/ 1,0/20% | 1,0 | 9,0 | B57237-S109-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 2,2/20% | 2,2 | 7,0 | B57237-S229-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 2,5/20% | 2,5 | 6,5 | B57237-S259-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 4,7/20% | 4,7 | 5,1 | B57237-S479-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 5,0/20% | 5,0 | 5,0 | B57237-S509-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 7,0/20% | 7,0 | 4,2 | B57237-S709-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 10,0/20% | 10,0 | 3,7 | B57237-S100-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 15,0/20% | 15,0 | 3,0 | B57237-S150-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 22,0/20% | 22,0 | 2,8 | B57237-S220-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |
| ▼ S237/ 33,0/20% | 33,0 | 2,5 | B57237-S330-M | 50 | 2000 | 1,46 | 1,25 | 1,08 | -96 | -84 |