

ULVH431

LINEAR INTEGRATED CIRCUIT

LOW-VOLTAGE ADJUSTABLE PRECISION SHUNT REGULATOR

■ DESCRIPTION

The UTC **ULVH431** is a low-voltage 3-terminal programmable shunt regulator with guaranteed thermal stability over full applicable industrial and commercial temperature ranges.

The output voltage of UTC **ULVH431** can be set to any value between V_{REF} (1.24V) and the corresponding maximum cathode voltage (18V) with two external resistors.

The UTC **ULVH431** is an ideal voltage reference in isolated feedback circuits for 3-V to 3.3-V switching-mode power supplies when it is used with an opto-coupler. It has a typical output impedance of 0.25Ω . Active output circuitry supplies a very sharp turn-on characteristic, which makes the UTC **ULVH431** very good substitute for low-voltage Zener diode in many applications such as adjustable power supplies and on-board regulation.

■ FEATURES

- * Adjustable output voltage, $V_O=V_{REF}$ to 18 V
- * Low-Voltage operation: $V_{REF}= 1.24$ V
- * Wide operating cathode current range: $100\mu A$ to $50mA$
- * Reference voltage tolerances at $25^\circ C$
- * $0.25-\Omega$ typical output impedance
- * $-40^\circ C \sim 125^\circ C$ specifications

■ ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
ULVH431L-AB3-R	ULVH431G-AB3-R	SOT-89	Tape Reel
ULVH431L-AE2-R	ULVH431G-AE2-R	SOT-23-3	Tape Reel
ULVH431L-AE3-R	ULVH431G-AE3-R	SOT-23	Tape Reel
ULVH431NSL-AE3-R	ULVH431NSG-AE3-R	SOT-23	Tape Reel
ULVH431L-AE5-R	ULVH431G-AE5-R	SOT-23-5	Tape Reel
ULVH431L-AF5-R	ULVH431G-AF5-R	SOT-25	Tape Reel


Note: Pin Code: R: Reference K: Cathode A: Anode

 ULVH431G-AB3-R	(1) R: Tape Reel
	(2) AB3: SOT-89, AE2: SOT-23-3, AE3: SOT-23
	AE5: SOT-23-5, AF5: SOT-25
	(3) G: Halogen Free and Lead Free, L: Lead Free

■ MARKING

SOT-23-3/SOT-23 (ULVH431)	SOT-23-3/SOT-23 (ULVH431NS)
SOT-89	SOT-23-5/SOT-25
Date Code ← L: Lead Free G: Halogen Free 1	


■ PIN CONFIGURATION



■ PIN DESCRIPTION

PIN NO.				PIN NAME	DESCRIPTION
SOT-23-3/SOT-23		SOT-23-5 SOT-25	SOT-89		
ULVH431	ULVH431NS				
1	2	4	1	REF	Reference voltage
2	1	3	3	CATHODE	Cathode voltage
3	3	5	2	ANODE	Anode voltage
-	-	1, 2	-	NC	No Connection

- BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	RATINGS	UNIT
Cathode Voltage (Note 1)	V_{KA}	20	V
Cathode Current Range	I_K	50	mA
Reference Current Range	I_{REF}	-0.05 ~ 3	mA
Operating Virtual Junction Temperature	T_J	+150	°C
Operating Temperature (Note 2)	T_{OPR}	-40 ~ +125	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. It is guarantee by design, not 100% be tested.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Package Thermal Impedance	θ_{JA}	325	°C/W
		125	°C/W


■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Cathode Voltage	V_{KA}	V_{REF}		18	V
Cathode Current (Continuous)	I_K	0.1		50	mA
Operating Free-Air Temperature Range	T_A	-40		+125	°C

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ free-air temperature, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS			MIN	TYP	MAX	UNIT	
Reference Voltage	V_{REF}	$V_{KA}=V_{REF}$, $I_K=10\text{mA}$	$T_A=25^\circ\text{C}$	$ULVH431\text{-A } (\pm 0.5\%)$	1.234	1.24	1.246	V	
				$ULVH431\text{-1 } (\pm 1\%)$	1.228	1.24	1.252	V	
				$ULVH431\text{-2 } (+2\%)$	1.252		1.265	V	
				$ULVH431\text{-3 } (-2\%)$	1.215		1.228	V	
V_{REF} Deviation Over Full Temperature Range	$V_{REF(dev)}$	$V_{KA}=V_{REF}$, $I_K=10\text{mA}$ (see Figure 1)				11	31	mV	
Ratio of V_{REF} Change to Cathode Voltage Change	$\frac{\Delta V_{REF}}{\Delta V_{KA}}$	$I_K=10\text{mA}$ (see Figure 2), $V_{KA}=V_{REF}\sim 18\text{V}$				-1.5	-2.7	mV/V	
Reference Terminal Current	I_{ref}	$I_K=10\text{mA}$, $R1=10\text{k}\Omega$, $R2=\text{Open}$ (see Figure 2)				0.1	0.5	μA	
I_{ref} Deviation Over Full Temperature Range	$I_{ref(dev)}$	$I_K=10\text{mA}$, $R1=10\text{k}\Omega$, $R2=\text{Open}$ (see Figure 2)				0.15	0.5	μA	
Minimum Cathode Current for Regulation	$I_{K(min)}$	$V_{KA}=V_{REF}$ (see Figure 1)				60	100	μA	
Off-State Cathode Current	$I_{K(off)}$	$V_{REF}=0$, $V_{KA}=18\text{V}$ (see Figure 3)				0.02	0.1	μA	
Dynamic Impedance	$ Z_{KA} $	$V_{KA}=V_{REF}$, $f\leq 1\text{kHz}$, $I_K=0.1\text{mA}\sim 50\text{mA}$ (see Figure 1)				0.25	0.4	Ω	

■ EQUIVALENT SCHEMATIC



■ PARAMETER MEASUREMENT INFORMATION




Figure 1. Test Circuit for
 $V_{KA} = V_{REF}$, $V_O = V_{KA} = V_{REF}$




Figure 2. Test Circuit for $V_{KA} > V_{REF}$,
 $V_O = V_{KA} = V_{REF} \times (1 + R1/R2) + I_{ref} \times R1$








Figure 3. Test Circuit for $I_{K(off)}$

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.