

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML
Product code : 08933311

Manufacturer or supplier's details

Company : Wuerth India Pvt. Ltd.
Address : 703/704, Windfall, Sahar Plaza Complex
Andheri (East), Mumbai 400059
Telephone : +91 8828111830
Emergency telephone number : 1800 102 5061
E-mail address : customer.care@wuerth.in

Recommended use of the chemical and restrictions on use

Recommended use : Sealant


2. HAZARDS IDENTIFICATION**Manufacture, Storage and Import of Hazardous Chemicals Rules 1989****Classification**

Flammable gas

GHS Classification

Aerosols : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propane	74-98-6	$\geq 5 - < 10$
O,O',O''-(Methylsilyldiyl)trioxime 2-pentanone	37859-55-5	$\geq 2.5 - < 5$
Butane	106-97-8	$\geq 1 - < 5$
2-Pentanone oxime	623-40-5	$\geq 1 - < 2.5$
2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime	58190-62-8	$\geq 1 - < 5$
Carbon black	1333-86-4	$\geq 1 - < 5$
Dimethylbis[(1-oxoneodecyl)oxy]stannane	68928-76-7	$\geq 0.1 - < 0.25$

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11	Revision Date: 01/27/2021	SDS Number: 1835680-00009	Date of last issue: 11/16/2020 Date of first issue: 07/14/2017
-----------------	------------------------------	------------------------------	---

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for : Non-sparking tools should be used.

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11	Revision Date: 01/27/2021	SDS Number: 1835680-00009	Date of last issue: 11/16/2020 Date of first issue: 07/14/2017
-----------------	------------------------------	------------------------------	---

containment and cleaning up

Soak up with inert absorbent material.
 Suppress (knock down) gases/vapours/mists with a water spray jet.
 For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
Advice on safe handling	:	Do not breathe spray. Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep away from water. Protect from moisture. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Do not spray on an open flame or other ignition source.
Conditions for safe storage	:	Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
Materials to avoid	:	Do not store with the following product types: Self-reactive substances and mixtures Organic peroxides Oxidizing agents Flammable liquids Pyrophoric liquids Pyrophoric solids

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
 Date of first issue: 07/14/2017

Self-heating substances and mixtures
 Explosives

Recommended storage temperature : < 50 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	IN OEL
		STEL	1,000 ppm	ACGIH
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH
Dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7	TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber
 Break through time : > 480 min
 Glove thickness : > 0.6 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11	Revision Date: 01/27/2021	SDS Number: 1835680-00009	Date of last issue: 11/16/2020 Date of first issue: 07/14/2017
-----------------	------------------------------	------------------------------	---

- Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Propellant : Propane, Butane
- Colour : black
- Odour : characteristic
- Odour Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11	Revision Date: 01/27/2021	SDS Number: 1835680-00009	Date of last issue: 11/16/2020 Date of first issue: 07/14/2017
-----------------	------------------------------	------------------------------	---

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	1.25 g/cm ³
Solubility(ies) Water solubility	:	hydrolyses
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Water

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Hazardous decomposition products

Contact with water or humid air : 2-Pentanone oxime
Methyl Isobutyl Ketoxime

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Acute oral toxicity : LD50 (Rat): 1,234 mg/kg
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 1,782 mg/kg
Remarks: Based on data from similar materials

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: vapour

2-Pentanone oxime:

Acute oral toxicity : LD50 (Rat): 1,133 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 1.22 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

Acute oral toxicity : LD50 (Rat): > 1,000 - < 2,000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
Remarks: Based on data from similar materials

Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 892 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rabbit
Result : No skin irritation

Carbon black:

Species : Rabbit
Result : No skin irritation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

2-Pentanone oxime:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Carbon black:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Bovine cornea
Method : OECD Test Guideline 437
Result : No eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**2-Pentanone oxime:**

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

Remarks : Based on data from similar materials

Carbon black:

Test Type : Buehler Test
 Exposure routes : Skin contact
 Species : Guinea pig
 Method : OECD Test Guideline 406
 Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:
Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Rat
 Application Route: inhalation (gas)
 Method: OECD Test Guideline 474
 Result: negative

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: positive

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 474
 Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2-Pentanone oxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 475
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Method: OECD Test Guideline 479
Result: negative

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Species: *Drosophila melanogaster* (vinegar fly)
Application Route: Ingestion
Method: OECD Test Guideline 477
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:**Carbon black:**

Species : Rat
Application Route : Inhalation
Exposure time : 24 Months
Result : positive

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Not classified based on available information.

Components:**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

2-Pentanone oxime:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Carbon black:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Result: negative

Test Type: Embryo-foetal development
Species: Mouse
Application Route: inhalation (dust/mist/fume)
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Effects on foetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:**Propane:**

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:**2-Pentanone oxime:**

Exposure routes : Ingestion
Target Organs : Blood, spleen
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Exposure routes : Ingestion
Target Organs : Nervous system
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Repeated dose toxicity**Components:****Propane:**

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone oxime:

Species : Rat
NOAEL : 15 mg/kg
LOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rat
NOAEL : > 10 - 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Rat
NOAEL : < 10 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Components:****Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Inhalation : Target Organs: Nervous system

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: > 21.5 mg/l
Exposure time: 28 d

2-Pentanone oxime:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Toxicity to microorganisms : EC50: > 20 mg/l
Exposure time: 28 d

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 117 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 117 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 103 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 37 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC0: > 22.2 mg/l
Exposure time: 28 h
Remarks: Based on data from similar materials

Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l
Exposure time: 24 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version 1.11 Revision Date: 01/27/2021 SDS Number: 1835680-00009 Date of last issue: 11/16/2020
Date of first issue: 07/14/2017

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 7.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Persistence and degradability**Components:****Propane:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

2-Pentanone oxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Butane:**

Partition coefficient: n-
octanol/water : log Pow: 2.31

2-Pentanone oxime:

Partition coefficient: n-
octanol/water : log Pow: 1.43

2-Pentanone, O,O',O''-(ethenylsilylidine)trioxime:

Partition coefficient: n-
octanol/water : log Pow: 1.25

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Partition coefficient: n-
octanol/water : log Pow: 5.503
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1

IATA-DGR

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

16. OTHER INFORMATION**Further information**

Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
---	---	---

SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-200ML

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

Date format : dd.mm.yyyy

Full text of other abbreviationsACGIH : USA. ACGIH Threshold Limit Values (TLV)
IN OEL : India. Permissible levels of certain chemical substances in work environment.ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
IN OEL / TWA : Time-Weighted Average Concentration (TWA) (8 hrs.)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SAFETY DATA SHEET



**SILSEAL-HIGHTEMP-(SUPER-RTV)-BLACK-
200ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
1.11	01/27/2021	1835680-00009	Date of first issue: 07/14/2017

IN / EN