


Part Number: SL12 1R010

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL12 1R010-A



### Electrical Specifications:

Resistance @ 25°C	1.0 Ω ± 20%
Max Steady State Current Up to 65°C	10.0 A
Max Recommended Energy Rating (Joules)	28.0 J
Actual Failure Point of Instantaneous Energy (Joules)	56.0 J
Resistance @ 100% of Max Current	0.027 Ω
Resistance @ 50% of Max Current	0.060 Ω
Body Temperature @ 100% Current Rating	182 °C
Dissipation Constant	12.7mW/°C
Thermal Time Constant	47 seconds
Max Recommended Voltage	265 V <sub>rms</sub>
Material Type	"A"
Max Recommended Capacitance @ 120VAC/240VAC	1900μF/475μF

### Mechanical Specifications:

D	12.0 ± 1.0 mm
T	4.0 ± 0.2 mm
Lead Diameter	0.8 ± 0.05 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads Coating Run Down	5.1 ± 0.5 mm
B	5.65 ± 0.75 mm
C	2.15 ± 0.30 mm