

# Light Emitting Diodes

Surface Mount LEDs

ADLSM Series





ADLSM3-1608-C200-S1



## INTRODUCTION

GREEN

The Adiva Surface Mount LED has a wide range of applications and a very small size enabling it to be used in a variety of advanced technological equipment such as cellular phones, PDAs, portable MP3 players and indicator lights.



(Unit:mm)




## ABSOLUTE MAXIMUM RATINGS

Items	Symbols	Ratings	Unit
Operation Forward Current	$I_f$	20	mA
Dominant wavelength	$\lambda_D$	570	mcd
Operating Temperature Range	$T_{Op}$	-25 ~ 80	C
Power Dissipation	$P_D$	75	mW
Reverse Voltage	$V_r$	5	V
Storage Temp. Range	$T_s$	-30 ~ 100	C
Soldering Temperature	$T_{sol}$	* 240	C

## FEATURES

- High Luminous intensity, with a longer operation life.
- Excellent consistency on color, intensity and Forward Current.
- Low voltage DC operated.
- Excellent Solderability and resistance to soldering heat.
- High Reliability, 100% Probing Test.
- Low thermal resistance

## RECOMMENDED SOLDERING PATTERN



## ELECTRICAL-OPTICAL CHARACTERISTICS

Parameter	Symbol	Conditions	Min.	Typ.	Max.
Forward Voltage	$V_f$	IF=20mA	1.9	--	2.5
Wavelength	(coord.)	IF=20mA	565	570	575
Luminous Intensity	mcd	IF=20mA	40	50	60

## SERIES STANDARD SPECIFICATIONS

Shape	Emitting Color	Part Number	Wavelength (nm)	Diffusion	IR( $\mu$ A) VR=10V MAX	Luminous Intensity (mcd) IF=20mA Typ	Emitting Material	Viewing Angle $\Theta$ (deg.)
0603	Green	ADLSM3-1608-C200-S1	570	W.C.	10	50	AlGaInP	120

Bin Ranking	S1			
IV (mcd)	40 - 60			