

Molex Legacy Products

Product Family	Overview	Pitch	Amperage	Circuit #	Orientation	Wire AWG
KK Series 	<p>Ideal for BtB and WtB low-power and signal applications, KK connectors provide a flexible design and cost-saving solutions.</p>	2.54mm — 3.96mm — 5.08mm	4.0A — 7.0A — 7.0A, 5.0A	2-36 — 2-24 — 2-12	WtB & BtB — WtB & BtB — WtB & BtB	22-30AWG — 18-26AWG — 18-26AWG
SL (Stackable Linear) 	<p>SL Modular Connectors deliver ideal WtW solutions varying PCB termination methods, including reflow capable versions and support a range of WtB applications</p>	2.54mm	3.0A +	2-25	WtB & BtB	22-36AWG
C-Grid 	<p>The 2.54mm pitch C-Grid products offer the largest number of variations and cabling configurations in the industry with both BtB and WtB options</p>	2.54mm	1.0A-3.0A	2-100	BtB & WtB <small>*Made WtB through using SL housings</small>	22-36AWG
C-Grid III 	<p>Interconnection system offering complete design flexibility and modular components that provide the widest range of electronic packaging alternatives</p>	2.54mm	3.0A	2-80	BtB & WtB	22-28AWG
Milli-Grid 	<p>A high-density connector system based on a 2.00 by 2.00mm grid pattern that offers complete design flexibility for both WtB and BtB applications</p>	2.0mm	2.0A	2-50	BtB & WtB	24-30AWG
Milli-Grid BMI 	<p>BMI interface that works for WtB applications to add extra assurance that connection is properly mated</p>	2.0mm	2.0A	4-20	WtB	24-30