


Part Number: SL08 4R003

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Not Available

For example: to order an inside kinked lead use part number SL08 4R003-A



Electrical Specifications:

Resistance @ 25°C	4.0 Ω \pm 20%
Max Steady State Current Up to 65°C	3.0 A
Max Recommended Energy Rating (Joules)	10.0 J
Actual Failure Point of Instantaneous Energy (Joules)	20.0 J
Resistance @ 100% of Max Current	0.234 Ω
Resistance @ 50% of Max Current	0.320 Ω
Body Temperature @ 100% Current Rating	122 °C
Dissipation Constant	9.0mW/°C
Thermal Time Constant	20 seconds
Max Operating Temperature	160 °C
Temperature Coefficient	-3.0%/°C

Mechanical Specifications:

D	8.0 \pm 0.5 mm
T	4.0 \pm 0.5 mm
Lead Diameter	0.5 \pm 0.1 mm
S	6.4 \pm 2.0 mm
L	38.0 \pm 3.0 mm
Straight Leads Coating Run Down	5.0 \pm 1.0 mm
B	5.00 \pm 1.00 mm
C	1.50 \pm 0.2 mm