

Part Number: SL22 20006-17

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL22 20006-17-A



Electrical Specifications:

Resistance @ 25°C	20.0 Ω ± 20%
Max Steady State Current Up to 65°C	6.0 A
Max Recommended Energy Rating (Joules)	125.0 J
Actual Failure Point of Instantaneous Energy (Joules)	250.0 J
Resistance @ 100% of Max Current	0.200 Ω
Resistance @ 50% of Max Current	0.420 Ω
Body Temperature @ 100% Current Rating	178 °C
Dissipation Constant	45.4mW/°C
Thermal Time Constant	104 seconds
Material Type	"H"
Max Voltage Rating	265VAC
Max Recommended Capacitance @ 120/240VAC	8650µF/2160µF

Mechanical Specifications:

D	20.0 ± 1.0 mm
T	5.0 ± 0.2 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads	5.0 ± 1.0 mm
Coating Run Down	
B	9.35 ± 0.85 mm
C	3.82 ± 1.0 mm