

CIR08T9-12W-XIW-101WF

LED T9 Tube Light, 9" OD, Frosted, 12W
100~277Vac, G10Q Socket, Warm White, 3000K
Angle of illumination: 120°



DWG BY:
USL / GP
08-28-14

R&D:
LUV
10-06-14

MFG:
LD
10-06-14

QA:
RD
10-06-14

REVISION LTR: A
ECR#: 100214-GP01
10-03-14



Top View



Side View



G10Q-F34 Included

Notes:

1. All Dimensions are in Inches [Millimeters].



○ **Electro-Optical Characteristics**

Input Voltage (typ)	100~277Vac
Tested @ (Voltage)	120Vac
Power Consumption	12W
Current Consumption	0.100 A
Efficacy: (Lm/W)	100
Lumens	1200 lm
Max Ft-Cd	320 cd
Power Factor	0.95
CRI (Ra)	80
CCT	3000K~3200K
Color	Warm White
R9	12.3
Angle of illumination	120°

○ **Features**

Operating Temperature	-10°C to +45°C
Storage Temperature	-20°C to +65°C
Heatsink Temperature	35°C
Base Material	Polycarbonate, White
Lens Material	Polycarbonate, Frosted White
LED LM80 Report	-
LM79 Report	-
Protection Rating	IP20
Dimmable	No
Life Span	40,000 hrs.
Warranty	5 Years
Weight	0.45 lbs.